

Economic consequences of optimized water management for a prolonged, severe drought in California

Julien J. Harou¹, Josué Medellín-Azuara², Tingju Zhu³, Stacy K. Tanaka⁴, Jay R. Lund², Scott Stine⁵, Marcelo A. Olivares⁶, Marion W. Jenkins²

¹Environment Institute and Department of Civil, Environmental and Geomatic Engineering, University College London, London, UK

²Department of Civil and Environmental Engineering, University of California, Davis, USA

³International Food Policy Research Institute, Washington, DC, USA

⁴Watercourse Engineering, Davis, California, USA

⁵Department of Geography, California State University – East Bay, USA

⁶Department of Civil Engineering, University of Chile, Santiago, Chile

ABSTRACT

If abrupt climate change has occurred in the past and may be more likely under human forcing, it is relevant to look at the adaptability of current infrastructure systems to severe conditions of the recent past. Geologic evidence suggests two extreme droughts in California during the last few thousand years, each 120-200 years long, with mean annual streamflows 40% - 60% of the historical mean. This study synthesized a 72-year drought with half of mean historical inflows using random sampling of historical dry years. One synthetic hydrological record is used and sensitivity to different interpretations of the paleorecord is not evaluated. Economic effects and potential adaptation of California's

water supply system in 2020 to this drought is explored using a hydro-economic optimization model. The model considers how California could respond to such an extreme drought using water trading and provides best case estimates of economic costs and effects on water operations and demands. Results illustrate the ability of extensive, intertied, and flexible water systems with heterogeneous water demands to respond to severe stress. The study follows a different approach to climate change impact studies, focusing on past climate changes from the paleo record rather than downscaled general circulation model results to provide plausible hydrologic scenarios. Adaptations suggested for the sustained drought are similar for dry forms of climate warming in California, and are expensive but not catastrophic for the overall economy, but would impose severe burdens on the agricultural sector and environmental water uses.

INTRODUCTION

Abrupt and widespread climate changes with major impacts have occurred repeatedly in the past and it is conceivable that human activity is increasing the probability of large-scale, rapid changes. Economic and ecological impacts of new climatic conditions on existing systems could be large and potentially serious. These impacts and the measures available to adapt current systems to severe conditions should be considered by policy-makers [Alley, *et al.*, 2003]. After abrupt change, it would be necessary to adapt existing infrastructure and management practices to new conditions. Although recent human-induced climate change may drastically change historical climate patterns, given the uncertainty of future climate water managers often rely on hydrologic conditions from the recent past to make decisions [Loaiciga, 2005]. Reconstructions of large paleodroughts (historical droughts deduced from geological records) provide an additional method of characterizing extreme climate periods to help evaluate existing system robustness under severe droughts, identify infrastructure and institutional adaptation measures, and take a long-term perspective on drought management policy.

Climate varies over decades, even centuries, sometimes having precipitation rates and other climate characteristics well beyond historical-scale variability. In the past decade future climate warming has raised concerns for how managed water systems could perform and adapt under very different climates. The development of hydrologic scenarios for such studies typically relies on general circulation models of climate (GCMs) with coarse results downscaled to local precipitation and temperatures, for use in

basin rainfall-runoff models. These studies are rarely definitive because of the ever-evolving and multiplying nature of GCM models, the difficulties and uncertainties of downscaling, and the uncertainties of rainfall-runoff models applied to circumstances and climates likely to be very different from those under which rainfall-runoff models were calibrated. Furthermore, changes predicted by these models mostly occur at the decadal to century scale, giving societies ample time to adapt their infrastructure and management practices. This being said, most GCMs in North America have shown a reduction of snowpack which should increase vulnerability to drought [*Christensen, et al.*, 2004; *Stewart, et al.*, 2004].

The geologic record has shown repeatedly that environmental change can come swiftly, with climate-driven hydrologic changes the main reason for shifts. This study takes a different and more extreme approach to examining water management under climatic change by focusing on severe and prolonged droughts from the paleorecord. Indications of severe and sustained mediaeval droughts in the past thousand years in California [*Stine*, 1994] are the basis in this study for developing a synthetic severe drought record for California. A synthetic drought of 72 years based on geologic observations is used in an economic-engineering optimization model of water management in California. The results provide a preliminary indication of the ability of California's water management system to respond to such severe, but apparently not unprecedented droughts, and provide insights into the potential magnitude and management of drought disasters for the state.

Use of the paleohydrologic record inscribed in historical, biological or geological memory is an accepted but infrequent approach in hydrologic engineering. One method is dendrohydrology, or tree ring research. Loaiciga et al. [1993] and Loaiciga [2005] describe how tree-ring based hydrologic reconstructions can help discern patterns of long-term hydrologic variability and aid in storage infrastructure design; Cook et al. [1999] and Meko et al. [1995] use the technique to identify historical droughts in the United States. Stedinger and Cohn [1986] and others have found historical and paleohydrologic information beneficial in flood frequency analysis.

Drought impacts on water resource and economic systems can be significant. Harding et al. [1995] simulate current system wide effects of a 38 year Colorado River paleodrought. They identify equity of allocation between states, loss of water quality, and loss of hydropower as major issues. Sangoyomi and Harding [1995] and Booker [1995] evaluate possible institutional responses to prolonged drought for the Colorado River System. Economic impacts of droughts can be considerable, particularly in agricultural economies where supply cannot be economically obtained by other means. Hydro-economic models [Harou, et al., submitted] can help evaluate the economic costs of water scarcity during droughts and propose engineering and institutional responses [Booker, 1995; Booker, et al., 2005; Ward, et al., 2006]. Our study shares this economic-engineering method [Lund, et al., 2006].

EXTREME PALEODROUGHTS IN CALIFORNIA

Several geologic, dendrohydrologic (tree-ring), and other studies of Holocene (geological epoch beginning 12,000 years ago) in California indicate severe and sustained droughts (up to 200 years) in the last millennium [*Brunelle and Anderson, 2003; Cook, et al., 2004; Ingram, et al., 1996; Starratt, 2001; Stine, 1990a; b; 1994*]. According to Stine [1990a; 1994], two major droughts occurred in the last millennium, roughly from 930-1130 AD, and from 1250-1350. During these two droughts, levels of Mono Lake and other Sierra Nevada Lakes declined well below recent diversion-induced lows, as evidenced by in-situ mature tree-trunks dated from these periods. These tree-ring records, with carbon dating, indicate prolonged droughts severe and sustained enough to reduce inflows to Mono Lake by 40-60% during the drought, without any period of wet years sufficient to raise the lake level enough to inundate and drown these trees. These droughts were apparently not unique to the Mono Basin. Along the Sierra Nevada range, there are similar indications of sustained drought during these same periods [*Stine, 1994*]. For many large (Tahoe) and small (Tenaya) Sierra Nevada Lakes, inflow was reduced sufficiently to prevent many natural lakes from over-topping their current rims and contributing to Central Valley streamflows, as evidenced from tree stumps dated from this period lying below these lake outlet elevations.

There is some evidence to dispute the spatial and temporal extent of these extreme droughts. Meko, et al. [2001] develop a tree-ring based hydrology from the Sacramento River from A.D. 869 to 2000 which shows several low flow periods during the Stine droughts but does not support their uninterrupted nature. The Sacramento River is the

largest single source of water for California's urban and agricultural water supply system. However, Meko et al. [2001] support that "the tree-ring record also suggests that persistently high or low flows over 50-year periods characterize some parts of the long-term flow history". Pollen-based reconstructions of climate by Davis [1999] generally match the Mono Lake fluctuations proposed by Stine [1990a], although fewer fluctuations are recorded. A sufficient number of studies identify periods of prolonged drought in the past to warrant the attention of current water managers and leads to the question whether such long-term fluctuations are observed more recently.

Meko and colleagues identify a 20 year drought in the late 1500s with mean annual Colorado River flow at 80% of historical mean [*Meko, et al., 1995; Meko and Woodhouse, 2005*]. These studies and others like them show prolonged drought is not restricted only to the geologic past and naturally dry periods in addition to human-induced warming remain a possibility. Furthermore, these studies point to the possibility of abrupt climate change, which from a water management perspective is very different from the drying trends investigated in most GCM-led adaptation studies [*Hulme, 2003*]. Because larger, faster and less-expected climate changes can cause more problems for economies and ecosystems, paleoclimatic data suggest the future may be more challenging than anticipated in current policy making [*Alley, 2003*].

METHOD

Synthetic drought

The character of the two droughts chosen for study in this work are of a sustained 100-200 year nature, with mean flows averaging 40-60% of current mean flows, and devoid of single or multiple very wet years sufficient to over-top these natural lake rims. A synthetic hydrologic record for a similar extreme drought covering all of California was developed by re-sampling surface flows from the historical record (1922-1993). The synthetic a set of hydrologic inflows averages 53% of the historical mean. This was done by random re-sampling from the ten driest years of record, since no “wet” years seemed to have occurred in the extreme droughts in the geologic record [Stine, 1994]. The same ordering of dry years was used to establish time series of surface water inflows (**Error! Reference source not found.**), groundwater inflows, local accretions (intra-basin runoff), seepage losses in rivers and environmental minimum flows for California’s water resource system. Most hydrologic time-series are taken from the CALSIM simulation model [Draper, et al., 2004]. Figure 1 shows how the persistent nature of the drought is captured by the synthetic record. Average total inflow to modeled areas is reduced from 48 km³ (historical) to 25.6 km³ for the synthetic drought (39 to 21 maf, million acre-feet). Sensitivity of model results to the particular random sequence of dry years was not evaluated for several reasons including the time required to interpret the large quantity of results from a single run. Because the variability of inflows within the 10 driest years of record is low (**Error! Reference source not found.**), and because the multi-period optimization model stores water optimally over time to avoid the worst shortfalls, the actual sequence of more or less ‘wet’ dry years is relatively insignificant in the context of

this study. Results aren't given for particular periods of the time horizon; rather we present only broad responses over the entire time horizon

Hydro-economic model

The CALVIN (CALifornia Value Integrated Network), hydro-economic optimization model of water supply management covers the entire inter-tied water supply system of California (**Error! Reference source not found.**) [Draper, *et al.*, 2003]. It includes all major inflows, surface and groundwater reservoirs, conveyance infrastructure, pumping, water and wastewater reuse treatment, and potential desalination facilities. No hydrologic modeling is performed in CALVIN; it is a management model that uses pre-established monthly time-series of flows produced by empirical data and/or simulation models.

The model optimizes monthly water management over a 72-year historical hydrologic record (1921-1993) for a particular level of infrastructure, population and land use development (projected to the year 2020 in this case). The operating rule of the optimization model, i.e. the objective function, is to minimize statewide costs from water scarcity and water operations by allocating, storing and trading water throughout the network; sunk capital costs are not included. Water demands are represented by economic penalty functions derived from agricultural and urban economic demand curves for water. Penalty functions represent the economic value lost when a water demand receives less than their target water delivery. Target deliveries indicate where more water

would not increase net benefits. Agricultural demand curves are estimated by the State-wide Agricultural Production (SWAP) model [Howitt, et al., 2001] and urban demand curves were taken from published sources [Jenkins, et al., 2003]. Examples of such functions are given by Draper et al. [2003]. Operating costs for pumping, artificial recharge, desalination and water treatment also are included.

CALVIN employs the Prescriptive Reservoir Model (HEC-PRM) software [USACE, 1999] as its computational and organizational core. HEC-PRM uses a computationally efficient generalized network flow linear optimization formulation that represents the system as a network of nodes and links. The model minimizes costs subject to flow continuity at nodes and capacity constraints on links; it can be written $Min \sum_i \sum_j c_{ij} X_{ij}$ subject to $\sum_i X_{ji} = \sum_i a_{ij} X_{ij} + b_j \forall j$, $X_{ij} \leq u_{ij} \forall ij$, $X_{ij} \geq l_{ij} \forall ij$, where X_{ij} is flow from a node i towards node j (link ij) and X_{ji} is flow from node j to a node i (link ji), c_{ij} = costs of flow through link ij (scarcity costs or operational costs), b_j = external inflows to node j , a_{ij} = gain/loss coefficient on flows in link ij , u_{ij} = upper bound (capacity) on link ij , and l_{ij} = lower bound on link ij . This generalized network flow formulation precludes including constraints beyond flow continuity at nodes and capacity constraints on links. The number of links (1,617) multiplied by the number of time periods (864) gives the minimum number of X_{ij} decision variables (1,397,088) (can increase due to piece-wise linearization). The model solves in approximately 12 hours using an initial solution on a 2 GHz PC.

Model results include time series of optimized monthly operations and water allocations to maximize statewide net economic benefits. This includes changing surface and groundwater operations and reallocating water to maximize net economic benefits (by minimizing net economic costs) within environmental flow, capacity, and mass balance constraints. Whenever and wherever optimal flow in the network is constrained, effect on the state's overall economic benefits are recorded as shadow values (Lagrange multipliers) providing valuable insights. Because of the monetary objective function, the network flow program's two constraint types have economically interpretable shadow values. Shadow values of capacity constraints (minimum or maximum storage or conveyance) provide the system-wide benefit that would result if the constraint were relaxed by 1 unit (e.g. if canal or reservoir capacity were increased). In the case of environmental flow constraints (minimum flows), shadow values provide the system-wide opportunity costs (foregone benefits) of the restrictions. Shadow values of mass balance constraints indicate for each time period and node how the objective function would change if an extra unit of water were available. This provides information on system-wide marginal value of increased local water deliveries.

Scenarios

The model has been applied previously with perturbed historical hydrologic inflows derived from GCM models to represent climate warming [*Medellín-Azuara, et al.*, 2008; *Tanaka, et al.*, 2006]. Here, the perturbed hydrology is a synthetic time-series designed to approximate one of California's major medieval droughts. We investigate economic

and water management effects if a severe dry period would befall the current system, and compare it with operation under current climate and management.

Three scenarios are modeled with water management infrastructure and water demands for the year 2020: a) A ‘Base Case’ constrains operations and allocation policies to emulate historical allocation policies, b) a ‘Historical’ climate scenario optimizes assuming institutional flexibility and economically-driven operation with historical hydrology and c) a ‘Drought’ scenario optimizes assuming institutional flexibility and economically-driven operation with the extreme drought hydrology. The base case scenario reflects historical operating policies (e.g. water rights) and climate; its results are heavily constrained to emulate CALSIM simulation model results [Draper, *et al.*, 2004]. CALSIM aims to reproduce historical allocations and reservoir operations. Optimized scenarios b) and c) involve best-case costs and operations that could occur under economically optimal and institutionally unconstrained management.

RESULTS

Water scarcity and its economic cost

Water scarcity is defined here as the difference between modeled water deliveries and the water that users would use at zero marginal cost (target demands). Urban scarcity is concentrated mostly in southern California (**Error! Reference source not found.**) and changes little among the three scenarios (Table 1) due to high economic values for urban water use (a consequence of high willingness-to-pay for water). Agricultural scarcity

increases greatly under the extreme drought (Table 1) in all regions except southern California (**Error! Reference source not found.**). Southern California retains much agricultural water use under extreme drought because of relatively reliable Colorado River flows and limited conveyance capacity to urban coastal areas (limiting the ability to export Colorado River water there). These flows are secure because California has the first priority water right to flow of the Colorado River [Norviel, *et al.*, 1922]; in addition, farmers in the southern Californian desert have senior water rights to much of the Colorado River flow. So flows from Colorado are fixed in the model and do not reflect potential drought in that area.

Scarcity costs are calculated as the lost economic benefits to water demand areas if they receive less than their target demand. Urban scarcity costs are high in southern California due to infrastructure constraints, primarily the limited capacity of Colorado aqueduct; see Table 5. In the base case these costs are even higher due to additional water right constraints (**Error! Reference source not found.**) such as the historical water rights of Imperial, Palo Verde and Coachella irrigation districts, together amounting to 86% of California's Colorado River allocation.

Scarcity costs for the extreme drought under economically optimal operations are greatest for the agricultural sector except in southern California where urban scarcity costs dominate. Agricultural scarcity is low in the base case and historical scenarios, but increases greatly with the drought (Table 1). Scarcity costs are an order of magnitude larger in the drought than in the historical scenario. For the base case, permanent water rights transfers in southern California since 1997 are not taken into account; if they were,

base case urban scarcity in southern California would decrease. The appearance of urban scarcity costs and high willingness-to-pay for more water in Northern California are also significant in the extreme drought.

Operating costs

Operating costs and average unit operating costs incurred in the modeled scenarios appear in Table 2. These are obtained by multiplying estimated unit costs (pumping, treatment) of conveyance through a link by the amount of water passing through that link. These describe variable operating costs incurred through activities such as pumping and treating water. Both optimized scenarios produce similar total operating costs because the drought scenario involves lower deliveries which reduces pumping costs. The unit costs are higher for the extreme drought as would be expected since existing resources are more actively managed. Operating costs are always at least twice the scarcity costs, implying rises in energy costs could significantly affect operations and total cost.

Adaptive actions: infrastructure and trading

California has a wide variety of options to adapt to the water supply effects of a severe and prolonged drought. These options include traditional water supply reservoir operations, conjunctive use of surface and ground waters, urban and agricultural water use efficiency practices, desalination, water reuse and water markets. Optimization results suggest portfolios of actions that economically adapt to changes in climate & population, as discussed below.

The need of surface and groundwater storage is lessened for the prolonged extreme drought due to greatly decreased inflow and decreased inflow variability. The value of additional surface storage capacity becomes zero under the major paleodrought as even existing reservoirs never fill (**Error! Reference source not found.**).

Error! Reference source not found. shows seasonal and over-year statewide groundwater storage. Initial and end estimates of state storage in 1921 and 1993 were estimated from regional groundwater models then set as start and end model constraints. Seasonal draw-down and refill indicates annual wet and dry season refill and use of aquifers. The amplitude of these seasonal storage variations averages about 2-3 km³. The much longer period variations in groundwater levels, about 10-20 years, indicate the use of groundwater for drought storage. This over-year storage use of groundwater has an amplitude of about 20-30 km³ for the historical hydrology. Less aggressive use of groundwater is made with the prolonged drought because little wet-year surface water is available to recharge groundwater basins; inter-annual variation in groundwater storage is greatly reduced for the extreme drought.

Larger water scarcities give economic incentives for owners of high-priority water rights with low-valued water uses to sell water to more economically productive water uses. This water market is implicit in the objective function of the optimization model [*Jenkins, et al.*, 2004] and is increasingly characteristic of California's water management. Water markets facilitate both re-allocation of water from agriculture to growing urban uses, as

well as more economical operation of water resources to improve technical operating efficiency [Harou and Lund, 2008; Pulido-Velazquez, et al., 2004]. This reallocation is evidenced in **Error! Reference source not found.** and **Error! Reference source not found.** by the relative shift of water scarcity from urban to agricultural uses (limited in southern California by conveyance capacities).

Water transfers are effective enough to preclude need for sea water desalination in either optimized scenarios at the conservative cost of \$1.14/m³. Average annual waste-water reuse increases 40% from 91 million cubic meters (mcm) in the optimized historical scenario to 128 mcm/year with the extreme drought.

Marginal economic values

Average and monthly willingness-to-pay for additional water deliveries are produced for each individual economic demand area (Appendix). Willingness-to-pay is estimated by looking up monthly model deliveries in the water demand functions and reporting the slope (in \$/tcm). In the optimized historical scenario, the economic willingness-to-pay for additional water is very small in much of California. For the extreme drought, willingness-to-pay for additional water (or its equivalent from reuse or efficiency actions) greatly increases. Agricultural willingness-to-pay for additional water often exceeds \$100/tcm (thousand cubic meters), precluding lower-value crops for the extreme drought. Urban willingness-to-pay for additional water in Southern California commonly exceeds \$700/tcm, reflecting physical capacity limits for importing water to southern California.

In Northern California, urban willingness-to-pay for additional water is very low, since urban users can purchase supplies from lower-valued agricultural uses.

Environmental flows in the model are represented with constraints for minimum streamflows and water deliveries to wetlands. Time-series constraints were taken from existing operations models [Draper, *et al.*, 2003]. The model does not recommend new environmental flow standards, but rather indicates i) the physical unavailability of water to sustain current environmental flow levels with such a sustained drought and ii) the economic value of water used for non-economic ecological purposes. To ensure computational feasibility of the severe drought model (i.e. not violate mass-balance), environmental flow had to be reduced compared to those required for the historical model (Table 3). Environmental flows are reduced by various amounts (between 3% and 67%), some locations requiring large reductions. Most reductions occur through sampling environmental flow requirements of driest years as explained in the synthetic hydrology section; a few additional reductions had to be made for the solver to find a feasible solution (Table 3).

Average marginal economic (opportunity) costs of environmental flow requirements are supplied by model shadow values. Table 4 contains the monthly average marginal economic costs of selected environmental flow requirements in California as well as the monthly maximum over 72 years. These are the opportunity costs of environmental flows to urban, agricultural, and hydropower users of this water supply system. Even after a 12% total reduction in environmental flows to ensure feasibility, the opportunity

cost of meeting environmental flow deliveries increase substantially with the extended drought; from hundreds to thousands of \$/tcm for rivers and from tens to hundreds of \$/tcm for ecological refuges. These opportunity costs of environmental flows illustrate the likelihood of increased water management controversy with such a drought.

One location where opportunity costs are especially relevant is the Sacramento River Delta which flows into the Bay of San Francisco, due to the large flow volume involved, its importance for facilitating north-to-south water transfers during drought, and the fragility of its infrastructure [Lund, *et al.*, 2008]. Opportunity costs are largest during the summer irrigation season; and lowest in September, when environmental flow requirements are at their lowest (**Error! Reference source not found.**).

Changes in infrastructure value and hydropower production

With the severe drought, economic values for expanding surface storage capacity become zero as even existing reservoirs never fill. However, because of the generalized increase in water transfers under drought, enlarged conveyance infrastructure makes sense at several locations in California. Table 5 provides monthly average and monthly maximum marginal values of increasing conveyance capacity at selected canals, diversions and pipelines. The Colorado aqueduct has the highest value for more infrastructure due to its ability in the model to bring more water to southern California. In a few cases, the marginal value of expanding conveyance capacity decreases due to reduced availability of water to convey.

Error! Reference source not found. shows monthly reservoir hydropower generation for the three scenarios. The paleodrought loses 60% of the state's hydropower production from water supply reservoirs when comparing both optimal scenarios, reflecting reductions in inflows.

DISCUSSION

Much of the great reduction in water available in the synthesized drought is from eliminating wet years when significant amounts of water are surplus to economic uses and “spill” from the system. This leads a 47% reduction in inflows to cause an order of magnitude increase in water scarcity and scarcity costs. The elimination of wet years especially tests the system's resiliency by not replenishing aquifer and reservoir storage. To understand the implications of this study it is important to understand the assumptions and limitations behind the approach, as summarized below.

A disadvantage of the re-sampling approach is that the entire synthetic drought record contains no single year drier than the driest year on the historical record. For such a drought, it seems likely that some years would be drier than the driest year from the historical hydrologic record. California's Colorado River supplies were not reduced beyond current $5.4 \text{ km}^3/\text{year}$ (4.4 maf) supplies whereas this share might be reduced under such extreme circumstances. A further limitation is that sensitivity to the random ordering of dry years is not evaluated.

Specific technical limitations of the CALVIN model are discussed elsewhere [Draper, *et al.*, 2003; Jenkins, *et al.*, 2004]. The most significant drawbacks relate to the a) use of a network flow formulation that limits ability to represent important physical phenomena (e.g. stream-aquifer interaction, dynamic pumping costs, etc.) and grants perfect hydrologic foresight to the optimization, b) non-consideration of flood control and recreation benefits, and c) use of imperfect and simplified data. Generally, the approach and results of this study assume California water management is institutionally flexible enough to allow it to economically optimize water operations. While many water management and policy decisions are driven by economics, perfect economic rationality is unlikely to prevail. The onset of an extreme prolonged drought would require a period of structural and expectation adjustment for the society, economy, institutions, and water managers. This study describes optimal management attainable during the latter years of the drought, after water managers have realized the onset and implications of prolonged drought. Environmental impacts of such an extreme, sustained drought would be severe, probably locally catastrophic, and merit a separate study with an appropriate methodology.

CONCLUSIONS

A synthetic version of a geologically/dendrohydrologically inferred prolonged medieval drought is used to study potential water supply effects of abrupt climate change in California. A single set of synthetic drought hydrologic time series with half (53%) of historical inflows is built by resampling the driest years of the historical record. A hydro-

economic optimization model is used to quantify economic and water management implications of the drought. Three scenarios were modeled: a constrained base case to represent current practices, an optimized historical run and an optimized drought scenario. Optimized scenarios assume pure economic optimization and pose no institutional constraints outside of ecological low flow limits.

Results for California's current water supply system showed that the economic cost of water scarcity under optimized drought management is roughly 5 times worse than the base case and 10 times worse than the optimally managed historical scenario. Scarcity costs were similar for the base case and drought scenarios, but they were an order of magnitude more than the optimized historical scenario. This implies scarcity costs even under efficient water management rise 10 fold under an approximate 50% reduction in inflows. Operating costs are always at least twice scarcity costs, indicating that scarcity costs under efficient management are not catastrophic on a statewide scale. Other indicators confirm the systems robustness under economically efficient management: desalination is not triggered at any time or place during the 72 year drought and wastewater reuse only increases by 40% as compared to the optimized historical scenario. Lower inflows imply reduced use of surface water and groundwater storage and no value for expanding storage capacity. Conveyance capacities showed high value of expansion, particularly in southern California where low supplies are heavily managed (i.e. conveyed). Opportunity costs of environmental low flows rose by 1 or more orders of magnitude with the extreme drought, pointing towards the high stakes competition for water that is inevitable under a severe prolonged drought.

California's current water storage, conveyance and treatment infrastructure allows adapting to severe prolonged drought despite severe economic and water supply effects to many regions. In the best case, optimal state-wide trading allows the water supply system to function without a catastrophic disruption to the statewide economy. However, the agricultural sector and environmental uses would face severe disruptions, and might be catastrophic for local ecosystems and communities. Effective response to such a severe and prolonged drought would require considerable institutional flexibility and use of water markets or other forms of water reallocation.

Appendix

The following table shows full regional results on deliveries, scarcity, scarcity costs and willingness-to-pay. Water volumes are in million cubic meters (mcm) or thousand cubic meters (tcm) per year.

Acknowledgements

This work was funded by the PIER program of the California Energy Commission. The authors thank three anonymous reviewers whose suggestions strongly improved the paper.

REFERENCES

- Alley, R. B. (2003), Palaeoclimatic insights into future climate challenges, *Philosophical Transactions of the Royal Society of London Series a-Mathematical Physical and Engineering Sciences*, 361, 1831-1848.
- Alley, R. B., et al. (2003), Abrupt climate change, *Science*, 299, 2005-2010.
- Booker, J. F. (1995), Hydrologic and Economic-Impacts of Drought under Alternative Policy Responses, *Water Resources Bulletin*, 31, 889-906.
- Booker, J. F., A. M. Michelsen, and F. A. Ward (2005), Economic impact of alternative policy responses to prolonged and severe drought in the Rio Grande Basin, *Water Resources Research*, 41.
- Brunelle, A., and R. S. Anderson (2003), Sedimentary charcoal as an indicator of late-Holocene drought in the Sierra Nevada, California, and its relevance to the future, *Holocene*, 13, 21-28.
- Christensen, N. S., A. W. Wood, N. Voisin, D. P. Lettenmaier, and R. N. Palmer (2004), The effects of climate change on the hydrology and water resources of the Colorado River basin, *Climatic Change*, 62, 337-363.
- Cook, E. R., D. M. Meko, D. W. Stahle, and M. K. Cleaveland (1999), Drought reconstructions for the continental United States, *Journal of Climate*, 12, 1145-1162.
- Cook, E. R., C. A. Woodhouse, C. M. Eakin, D. M. Meko, and D. W. Stahle (2004), Long-term aridity changes in the western United States, *Science*, 306, 1015-1018.

- Davis, O. K. (1999), Pollen analysis of a late-glacial and Holocene sediment core from Mono Lake, Mono County, California, *Quaternary Research*, 52, 243-249.
- Draper, A. J., M. W. Jenkins, K. W. Kirby, J. R. Lund, and R. E. Howitt (2003), Economic-engineering optimization for California water management, *Journal of Water Resources Planning and Management*, 129, 155-164.
- Draper, A. J., A. Munevar, S. K. Arora, E. Reyes, N. L. Parker, F. I. Chung, and L. E. Peterson (2004), CalSim: Generalized model for reservoir system analysis, *Journal of Water Resources Planning and Management*, 130, 480-489.
- Harding, B. L., T. B. Sangoyomi, and E. A. Payton (1995), Impacts of a Severe Sustained Drought on Colorado-River Water-Resources, *Water Resources Bulletin*, 31, 815-824.
- Harou, J. J., and J. R. Lund (2008), Ending groundwater overdraft in hydrologic-economic systems, *Hydrogeology Journal*, 16, 1039-1055.
- Harou, J. J., M. Pulido-Velazquez, D. E. Rosenberg, J. Medellin, J. R. Lund, and R. E. Howitt (submitted), Hydro-economic models: concepts, design, limitation and future directions, *Journal of Hydrology*.
- Howitt, R. E., K. B. Ward, and S. M. Msangi (2001), Appendix A: Statewide Water and Agricultural Production Model, , in *Improving California Water Management: Optimizing Value and Flexibility*, edited by M. W. Jenkins, et al., Center for Environmental and Water Resources Engineering, University of California, Davis, CA.

- Hulme, M. (2003), Abrupt climate change: can society cope?, *Philosophical Transactions of the Royal Society of London Series a-Mathematical Physical and Engineering Sciences*, 361, 2001-2019.
- Ingram, B. L., J. C. Ingle, and M. E. Conrad (1996), A 2000 yr record of Sacramento San Joaquin river inflow to San Francisco Bay estuary, California, *Geology*, 24, 331-334.
- Jenkins, M. W., J. R. Lund, and R. E. Howitt (2003), Using economic loss functions to value urban water scarcity in California, *Journal American Water Works Association*, 95, 58-+.
- Jenkins, M. W., J. R. Lund, R. E. Howitt, A. J. Draper, S. M. Msangi, S. K. Tanaka, R. S. Ritzema, and G. F. Marques (2004), Optimization of California's water supply system: Results and insights, *Journal of Water Resources Planning and Management*, 130, 271-280.
- Loaiciga, H. A. (2005), Drought, tree rings, and reservoir design, *Journal of the American Water Resources Association*, 41, 949-958.
- Loaiciga, H. A., L. Haston, and J. Michaelson (1993), Dendrohydrology and Long-Term Hydrologic Phenomena, *Reviews of Geophysics*, 31, 151-171.
- Lund, J., E. Hanak, W. Fleenor, W. Bennett, R. Howitt, J. Mount, and P. Moyle (2008), *Comparing Futures for the Sacramento-San Joaquin Delta*, 184 pp., Public Policy Institute of California (PPIC).
- Lund, J. R., X. Cai, and G. W. Characklis (2006), Economic Engineering of Environmental and Water Resource Systems, *Journal of Water Resources Planning and Management*, 132, 399-402.

- Medellín-Azuara, J., J. J. Harou, M. A. Olivares, K. Madani, J. R. Lund, R. E. Howitt, S. K. Tanaka, and M. W. Jenkins (2008), Adaptability and Adaptations of California's Water Supply System to Dry Climate Warming, *Climatic Change*, 87, S75–S90.
- Meko, D., C. W. Stockton, and W. R. Boggess (1995), The Tree-Ring Record of Severe Sustained Drought, *Water Resources Bulletin*, 31, 789-801.
- Meko, D. M., M. D. Therrell, C. H. Baisan, and M. K. Hughes (2001), Sacramento River flow reconstructed to AD 869 from tree rings, *Journal of the American Water Resources Association*, 37, 1029-1039.
- Meko, D. M., and C. A. Woodhouse (2005), Tree-ring footprint of joint hydrologic drought in Sacramento and Upper Colorado river basins, western USA, *Journal of Hydrology*, 308, 196-213.
- Norviel, W. S., W. F. McClure, D. E. Carpenter, J. G. Scrugham, J. Stephen B. Davis, R. E. Caldwell, and F. E. Emerson (1922), Colorado River Compact, edited by U. S. Government.
- Pulido-Velazquez, M., M. W. Jenkins, and J. R. Lund (2004), Economic values for conjunctive use and water banking in southern California, *Water Resources Research*, 40.
- Sangoyomi, T. B., and B. L. Harding (1995), Mitigating Impacts of a Severe Sustained Drought on Colorado-River Water-Resources, *Water Resources Bulletin*, 31, 925-938.
- Starratt, S. W. (2001), Diatoms as Indicators of Freshwater Flow Variation in Central California, in *PACLIM Conference Proceedings*, pp. 129-144, edited, <http://meteora.ucsd.edu/paclim/10Starratt.pdf>.

- Stedinger, J. R., and T. A. Cohn (1986), Flood Frequency-Analysis with Historical and Paleoflood Information, *Water Resources Research*, 22, 785-793.
- Stewart, I. T., D. R. Cayan, and M. D. Dettinger (2004), Changes in snowmelt runoff timing in western North America under a 'business as usual' climate change scenario, *Climatic Change*, 62, 217-232.
- Stine, S. (1990a), Late Holocene Fluctuations of Mono Lake, Eastern California, *Palaeogeography Palaeoclimatology Palaeoecology*, 78, 333-&.
- Stine, S. (1990b), Past Climate at Mono Lake, *Nature*, 345, 391-391.
- Stine, S. (1994), Extreme and Persistent Drought in California and Patagonia During Medieval Time, *Nature*, 369, 546-549.
- Tanaka, S. K., T. J. Zhu, J. R. Lund, R. E. Howitt, M. W. Jenkins, M. A. Pulido, M. Tauber, R. S. Ritzema, and I. C. Ferreira (2006), Climate warming and water management adaptation for California, *Climatic Change*, 76, 361-387.
- USACE (1999), HEC-PRM Package, edited, Hydrologic Engineering Center, U.S. Army Corps of Engineers, Davis, CA.
- Ward, F. A., J. F. Booker, and A. M. Michelsen (2006), Integrated economic, hydrologic, and institutional analysis of policy responses to mitigate drought impacts in Rio Grande Basin, *Journal of Water Resources Planning and Management-Asce*, 132, 488-502.

Figure Captions

Figure 1: Monthly and annual average surface water inflows in km³.

Figure 2: Hydrologic basins, demand areas, major inflows and facilities in CALVIN.

Figure 3: Average annual agricultural and urban water scarcity and deliveries. Notes: cf.

Figure 2 for geographic outlines of four regions summarized here. Total water demands and delivery targets do not vary by scenario.

Figure 4: Costs due to agricultural and urban water scarcity

Figure 5: Statewide annual surface water storage

Figure 6: Statewide groundwater storage with base case, historical and drought scenarios

Figure 7: Sacramento River Delta outflows and their opportunity costs. Note: bottom graphs have differing scale.

Figure 8: Monthly Reservoir Hydropower Generation (GWhr/mon).

Tables

Table 1: State-wide mean annual water scarcity and scarcity cost estimated by model.

Scenario	Water Scarcity (km ³ /year)			Water scarcity Cost (Million\$/year)		
	Agricultural	Urban	Total	Agricultural	Urban	Total
Base Case	0.9	1.1	2.0	26	1564	1590
Historical	1.0	0.2	1.1	33	89	123
Drought	8.5	0.8	9.3	1040	637	1677

Table 2: Average Annual Operating Costs and Unit Operating Costs estimated by model.

Scenario:	Operating Costs (\$M/yr)			Average Unit Operating Costs (\$/tcm)		
	Base Case	Historical	Drought	Base Case	Historical	Drought
Sacramento	247	200	182	20	16	19
San Joaquin	394	375	378	52	49	65
Tulare	461	920	936	36	71	91
Southern Cal.	3,074	1,974	1,901	257	161	162
<i>Total and Average</i>	4,176	3,468	3,396	93	76	91

Table 3: Average annual environmental flows in million cubic meters (mcm) for the historical and drought model runs and their reduction due to infeasibilities.

Environmental Flow Location	Historical	Reduction for synthetic drought	Reduction for computational feasibility	Drought	% Decrease in environmental flows
American River	191	73	0	118	38%
Trinity River	62	20	0	41	33%
Clear Creek	13	1.3	0	11	11%
Upper Sacramento River	736	92	83	561	24%
Lower Sacramento River	24447	615	166	23665	3%
Mokelumne River	36	24	0	12	67%
Calaveras River	7.1	0	2.9	3.9	45%
Stanislaus River	568	200	0	368	35%
Tuolumne River	799	330	0	468	41%
Merced River	242	43	0	199	18%
San Joaquin River	1272	687	0	585	54%
San Joaquin Refuge	57	5	0	52	9%
Mono Lake	7.6	0	1.5	6.1	20%
Delta	6899	1933	0	4966	28%
TOTAL	35334	4024	254	31056	12%

Table 4: Marginal economic opportunity costs of environmental flow requirements estimated by model (average monthly values in \$/tcm)

	Average Opportunity Cost		Maximum Opportunity Cost	
	Historical	Drought	Historical	Drought
Minimum Instream Flows				
Trinity River	28	40,781	47	114,150
Clear Creek	13	40,143	28	114,044
Sacramento River	0.2	286	5	113,618
Sacramento River at Keswick	1	32,238	16	113,150
Feather River	0.2	44	7	162
American River	0.4	62	8	846
Mokelumne River	2	1,767	8	2,804
Calaveras River	0	5	0	241
Yuba River	0	68	6	3,322
Stanislaus River	7	106	37	272
Tuolumne River	6	122	32	369
Merced River	7	70	23	274
Mono Lake Inflows	781	384	1158	1,931
Owens Lake Dust Mitigation	604	899	660	1,514
Refuges				
SacWestRefuge	2	140	7	745
SacEastRefuge	0.1	3	5	149
Volta Refuges	19	146	25	267
San Joaquin/Mendota Refuges	17	115	23	210
Pixley	26	256	39	328
Kern	31	165	37	231
Delta Outflow	1.9	81	6.7	170



Table 5: Monthly average and maximum (over 72 years) marginal value of conveyance capacity at selected sites estimated by model.


Conveyance infrastructure	Physical Capacity (tcm/month)	Average Marginal Value (\$/tcm)		Maximum Marginal Value (\$/tcm)	
		Historical	Drought	Historical	Drought
Colorado Aqueduct	134	118	224	283	962
Kings River Diversion	17	3	47	26	289
Sacramento River Diversion	13	0	41	0	808
American River Diversion	25	0	40	0	532
Cross Valley Canal	60	0	26	0	186
Kern Water Bank Canal	74	0	20	0	186
Auld Valley Pipeline	26	0	5	0	256
Arvin Edison intertie	15	0	5	0	170
SFPUC to Santa Clara Valley	17	0	3	0	99
Auld Valley Pipeline	26	1.2	0	6	0
San Diego Canal	127	0.3	0	77	0
Santa Ana Pipeline	35	0.2	0	77	0
MWD Feeders	112	0	0.1	0	19


Region	Type	Demand Area	Target mcm/yr	Base Case				Unconstrained Historical Hydrology				Unconstrained Drought Hydrology						
				Delivery mcm/yr	Scarcity mcm/yr	Scarcity %	Scarcity Cost \$/tcm	WTP \$/tcm	Delivery mcm/yr	Scarcity mcm/yr	Scarcity %	Scarcity Cost \$/tcm	WTP \$/tcm	Delivery mcm/yr	Scarcity mcm/yr	Scarcity %	Scarcity Cost \$/tcm	WTP \$/tcm
N. Cal	Ag	CVPM 1	189	189	0.4	0%	0.01	0	189	0	0%	0	0	40	149	79%	17.4	77
		CVPM 2	859	790	69.9	8%	3.5	28	859	0	0%	0	0	456	403	47%	53.8	103
		CVPM 3	2,009	1,903	105.7	5%	3.2	16	2,009	0	0%	0	0	1,337	672	33%	65.1	78
		CVPM 4	1,354	1,356	0	0%	0	0	1,354	0	0%	0	0	916	438	32%	39.2	79
		CVPM 5	2,142	2,144	0	0%	0	0	2,142	0	0%	0	0	1,681	461	22%	30.1	57
		CVPM 6	1,292	1,293	0	0%	0	0	1,292	0	0%	0	0	1,041	251	19%	22.2	89
		CVPM 7	697	697	0.4	0%	0	0	697	0	0%	0	0	544	153	22%	10.7	58
		CVPM 8	1,103	1,103	0	0%	0	0	1,103	0	0%	0	0	851	252	23%	22.3	92
		CVPM 9	1,461	1,451	9.6	1%	0.1	16	1,461	0	0%	0	0	1,262	199	14%	11.0	44
	Urb	Napa-Solano	142	129	13.1	9%	22.0	456	142	0	0%	0	0	142	0	0%	0	0
		Contra Costa	166	166	0.5	0%	0	15	166	0	0%	0	0	166	0	0%	0	0
		East Bay	367	358	9.2	3%	12.0	231	366	0.8	0%	0.6	22	257	109	30%	196.6	1981
		Mud	117	117	0	0%	0	5	117	0	0%	0	0	117	0	0%	0	4
San Joaquin	Ag	Stockton	837	838	0	0%	0	0	837	0	0%	0	0	836	0	0%	0.3	2
		Yuba	66	64	1.2	2%	0.9	44	66	0	0%	0	0	66	0	0%	0	0
		CVPM 10	2,095	2,095	0	0%	0	0	2,095	0	0%	0	0	1,888	207	10%	14.5	56
	Urb	CVPM 11	1,069	1,070	0	0%	0	0	1,066	2.4	0%	0.06	0.9	419	650	61%	117.9	144
		CVPM 12	990	990	0	0%	0	0	989	1.4	0%	0.04	0.3	593	397	40%	56.0	162
		CVPM 13	2,332	2,334	0	0%	0	0	2,332	0	0%	0	0	1,787	546	23%	67.5	141
		San Francisco	294	286	7.6	3%	5.0	191	294	0	0%	0	0	294	0	0%	0.05	6
		Santa Clara	810	797	12.3	2%	10.0	164	810	0	0%	0	0	810	0	0%	0	0


	V.																
	CVPM 14	1,845	1,847	0	0%	0	0	1,845	0	0%	0	0	1,086	759	41%	219.2	158
	CVPM 15	2,457	2,446	10.5	0%	0.4	26	2,457	0	0%	0	0	1,989	468	19%	45.5	100
	CVPM 16	611	615	0	0%	0	0	605	6	1%	0.1	13	517	95	16%	13.7	164
	CVPM 17	1,030	1,032	0	0%	0	0	1,012	17	2%	0.4	15	809	221	21%	29.7	178
	CVPM 18	2,664	2,392	272.7	10%	18.8	106	2,664	0	0%	0	0	1,827	837	31%	125.1	156
	CVPM 19	1,180	1,181	0	0%	0	0	1,180	0	0%	0	0	1,042	138	12%	14.0	80
	CVPM 20	835	835	0	0%	0	0	835	0	0%	0	0	713	122	15%	14.9	121
	CVPM 21	1,433	1,433	0.1	0%	0	0	1,433	0	0%	0	0	1,287	146	10%	18.0	95
	Fresno	469	417	51.9	11%	18.0	311	469	0	0%	0	0	468	1	0%	0.4	53
	Bakersfield	321	323	0	0%	0	0	321	0	0%	0	0	321	0	0%	0	0
	SB-SLO	171	172	0	0%	0	0	171	0	0%	0	0	171	0	0%	0	0
	Palo Verde	973	815	157.2	16%	1.4	14	619	354	36%	10.2	58	619	354	36%	10.2	58
	Coachella	241	240	0.6	0%	0	0	223	18	7%	1	50	223	18	7%	0.9	50
	Imperial	3,370	3,146	224.1	7%	4.4	15	2,807	563	17%	21.5	60	2,807	563	17%	21.5	60
	San Bernardino	348	344	4.6	1%	4.0	207	348	0	0%	0	0	322	26	8%	13.7	559
	Mojave	434	277	157.3	36%	181.0	1004	427	7	2%	2.9	138	387	47	11%	23.8	594
	Central MWD	4,602	4,360	241.3	5%	183.0	589	4,602	0	0%	0	0	4,298	303	7%	216.3	774
	Castaic Lake	158	55	102.8	65%	508.0	6901	147	11	7%	5.4	537	134	24	15%	15.0	749
	Antelope Valley	342	230	112.2	33%	185.0	1693	331	11	3%	6.5	606	314	28	8%	20.0	799
	San Diego	1,219	1,178	41.2	3%	35.0	409	1,219	0	0%	0	0	1,162	57	5%	44.1	769
	Coachella	741	429	311.9	42%	367.0	1000	618	123	17%	73.8	827	630	111	15%	63.7	739
	E&W MWD	913	872	41.0	4%	33.0	546	913	0	0%	63.9	1	856	57	6%	42.8	786
	TOTALS	46,749	44,809	1,959		1,596		45,635	1,114		186		37,487	9,262		1,677	
	Average	1,087	1,042	46	6%	37	325	1,061	26	2%	4	54	872	215	18%	39	238
	Average Agri	1,426	1,392	35	2%	1	9	1,386	40	3%	1	8	1,072	354	27%	43	100


Regions Average Urban Regions	659	601	58	12%	82	724	651	8	1%	8	112	619	40	5%	34	411
--	-----	-----	----	-----	----	-----	-----	---	----	---	-----	-----	----	----	----	-----

















Historical Delta Outflows**Drought Delta Outflows****Historical Opportunity Costs of Delta Outflows****Drought Opportunity Costs of Delta Outflows**