

Contents

Resumen	ii
Abstract	iii
Acknowledgements	iv
Abbreviations	xi
1 Introduction	1
1.1 Background	1
1.2 Hypotheses	3
1.3 Objectives	3
1.3.1 General objective	4
1.3.2 Specific objectives	4
1.4 Thesis organization	5
2 Theoretical Framework	7
2.1 Bayesian inference and Monte Carlo methods	7
2.1.1 Bayesian inference	7
2.1.2 Sequential Monte Carlo methods: Generic particle filter	9
2.1.3 Regularized particle filter	13
2.2 Tools for signal statistical characterization	15
2.2.1 Markov chains	15
2.2.2 Concentration inequalities	16
2.2.3 Hypothesis test to infer the order of Markov chains	17
2.3 Particle filter-based prognosis scheme for dynamic systems	18
2.3.1 Prediction for n-steps ahead: Regularized PF-based scheme	19
2.3.2 Statistical characterization of the End-of-Discharge and End-of-Life	20
3 Simulating Usage Profiles for Electric Vehicles	23
3.1 Battery pack: Electrical characterization	25
3.1.1 Data sources: AESC and DoE's Advanced Vehicles Testing Program	26
3.2 Vehicle mechanical parameters	29
3.3 Mission Map: Terrain characteristics	30

3.4	Driving schedules	32
3.5	Power demand for the EV mission completion	34
3.6	Cruise control: An alternative way to obtain the EV required power	35
3.7	EV current consumption: A deterministic usage profile	40
4	Battery Pack Autonomy: Filtering and Prognosis Schemes for the State-of-Charge	43
4.1	Metamodel A: An approximation to internal ohmic resistance	44
4.2	State space model for the SOC	46
4.3	Determination of the measurement equation parameters	48
4.4	Regularized particle filter applied to the SOC SS model	50
4.5	Probabilistic characterization of usage profiles based on Markov chains	53
4.5.1	Data clustering	53
4.5.2	Maximum likelihood estimation of transition probabilities	54
4.5.3	Number of states and order of the Markov chain	54
4.5.4	EV usage profile: A probabilistic model	55
4.6	Battery pack autonomy: Prognosis scheme applied to the SOC SS model	57
5	Battery Pack Remaining Life: Prognosis Schemes applied to the State-of-Health	63
5.1	Metamodel B: An approximation to Coulomb efficiency	64
5.2	State space model for the SOH	67
5.3	Battery pack remaining life: Prognosis scheme applied to the SOH SS model	69
5.4	Final considerations	74
6	Laboratory Data Acquisition: Individual Lithium-Ion Cell Discharges	77
6.1	Laboratory implementation	77
6.2	Experimental design	79
6.3	Preliminary results: Cell internal resistance	81
6.4	Preliminary results: Coulomb efficiency	82
6.5	Equipment requirements for ideal implementation	85
7	Conclusions	87
7.1	Future work	89
	Bibliography	90

List of Figures

2.1	A simple graphical representation of a first order homogeneous Markov chain of two states	16
3.1	A progression scheme to simulating usage profiles for EVs	24
3.2	General schematics for an ESS in an EV: specific Nissan Leaf example	25
3.3	Characterization of individual new lithium-ion cells at 25°C from AESC	27
3.4	Characterization of a Nissan Leaf battery pack from the DoE’s Advanced Vehicles Testing Program	28
3.5	Map and elevation profile of the route between two given cities	32
3.6	EPA vehicle dynamometer driving schedules	33
3.7	Power requisite to keep the EV at HWFET driving schedule speeds	35
3.8	Block diagram of a PI feedback system for cruise control	35
3.9	Optimization methods employed to find the cruise control PI gains	37
3.10	Performance results of the cruise control PI controller when taking into account elevation variations in the mission map	38
3.11	Power requisite to keep the EV at cruise control reference speed	39
3.12	EV current consumption: Simulated current and voltage profiles	41
4.1	Battery pack internal resistance as a function of SOC (DoE’s Advanced Vehicles Testing Program)	44
4.2	Procedure to derive the battery pack internal resistance as a function of current	45
4.3	Metamodel A: graphical representation of the pack internal resistance as a function of SOC and current	45
4.4	OCV curve fitting process	48
4.5	Detail of the OCV third zone fitting process	49
4.6	Results for the regularized PF estimation stage: Internal resistance and voltage profiles	51
4.7	Results for the regularized PF estimation stage: SOC curve	51
4.8	Upper probability bounds given by Hoeffding and Chebyshev inequalities for four valid states	55
4.9	Probabilistic model for the EV usage profile	56
4.10	Long-term prognosis for the internal impedance module and voltage of the battery pack	59

4.11	SOC long-term prognosis and EOD characterization	60
5.1	Schematics of the interplay between cycle operational conditions and SOH evolution	64
5.2	Metamodel B for medium dependency of η_C on DoD and discharged current intensity	65
5.3	Metamodel B for strong dependency of η_C on DoD and discharged current intensity	66
5.4	Metamodel B for weak dependency of η_C on DoD and discharged current intensity	67
5.5	Evolution of the DoD and current intensity in a degradation simulation	70
5.6	SOH long-term prognosis and EOL characterization (η_C medium dependence on I and DoD)	71
5.7	Kernel smoothed pdfs for the DoD and current intensity in a given discharge cycle	72
5.8	SOH long-term prognosis and EOL characterization (η_C strong dependence on I and DoD)	74
5.9	GUI for the simulation engine	75
6.1	Laboratory equipment for discharge tests of individual lithium-ion cells	78
6.2	Schematics of the proposed experimental design	80
6.3	A typical calibration discharge: Deriving internal resistance from voltage and current data	82
6.4	Internal resistance preliminary results for three lithium-ion cells	83
6.5	EB2 preliminary results: Capacity, OCV, discharge duration, end-condition and temperatures for ~ 100 cycles	84
6.6	EB3 preliminary results: Capacity, OCV, discharge duration, end-condition and temperatures for ~ 100 cycles	84
6.7	EB4 preliminary results: Capacity, OCV, discharge duration, end-condition and temperatures for ~ 100 cycles	85
7.1	General schematics for the EV simulation engine	88

List of Tables

3.1	EV battery pack characterization: input example for the 2015 Nissan Leaf . .	29
3.2	EV required parameters: input example for 2015 Nissan Leaf	30
3.3	Environmental (fixed) parameters	30
3.4	EPA vehicle chassis dynamometer driving schedules	33
4.1	Parameters of the SOC SS model measurement equation	49
4.2	Estimation stage: PF parameters in a single discharge process	52
4.3	Probabilistic characterization of the usage profile: Parameters of the algorithm	56
4.4	Long-term SOC prognosis parameters	57
4.5	Statistical characterization of the EOD for different realizations of the long-term SOC prognosis algorithm	58
5.1	Parameters of the SOH SS model	68
6.1	Data-sheet values for the ICR26650-type lithium-ion cylindrical cell	79