

Contents

1	Introduction	1
1.1	Hypothesis	3
1.2	Objectives	3
1.2.1	General Objective	3
1.2.2	Specific Objectives	4
1.3	Structure of the Thesis	4
2	Bibliographic Review	5
2.1	Optical Theory	5
2.1.1	Geometrical Optics	6
2.1.2	Quasioptical Theory	8
2.1.3	Radiation Pattern	10
2.2	Optical Devices	12
2.2.1	Cassegrain Antennas	13
2.2.2	Horn Antennas	15
2.2.3	Focusing Elements: Lenses and Mirrors	16
2.3	Heterodyne Receivers	20
2.3.1	Noise Temperature	21
2.4	Imaging Systems	22
2.4.1	Gaussian Telescope	23
2.4.2	Pixel distances	24
2.4.3	Pixel distribution	25
2.5	Revision of Existing Focal Plane Arrays	25
2.5.1	Submillimeter and Terahertz Regime	25
2.5.2	Millimeter Regime	27
2.6	Summary	27
3	Feasibility of a Camera in the SMWT	28
3.1	Brief History of the SMWT	28
3.2	Description of the Antenna	29
3.3	Simulations with the current feed antenna	30
3.3.1	Central Feed	30
3.3.2	Off-axis Feed	32
3.4	Simulations with a new feed antenna	35
3.4.1	Using the same aperture	35
3.4.2	Using an optimized aperture for a 7-pixel focal plane array	36

3.5	Analysis of the Results	37
3.6	Summary	38
4	Design of an Optical System for a W-Band Camera of a 12-m Antenna	39
4.1	ALMA project	39
4.2	Description of the ALMA 12-m antenna	40
4.3	Design considerations	41
4.4	Design of intermediate optics for ALMA Band-3	42
4.4.1	Restrictions for ALMA	42
4.4.2	Design of a Gaussian-Beam Telescope for ALMA Band-3 camera	45
4.4.3	Mechanical considerations for ALMA	48
4.5	Tolerances in construction and assembly	50
4.6	Analysis of results obtained for ALMA	51
4.7	LLAMA project	52
4.8	Description of the LLAMA 12-m antenna	52
4.9	Design of intermediate optics for LLAMA Band-3	53
4.9.1	Restrictions for LLAMA	53
4.9.2	Design of a Gaussian Beam Telescope for LLAMA Band-3 camera	55
4.9.3	Expansion of LLAMA's Band-3 Camera Using More Pixels	57
4.9.4	Mechanical considerations for LLAMA	58
4.10	Analysis of results obtained for LLAMA	58
4.11	Summary	59
5	Conclusion	60
5.1	Further Work	61
	Bibliography	62
A	Formulas for conic sections	68
B	ABCD matrix	69
C	Hexagonal distribution	71
D	Parameters of the SMWT in its original units	73
E	Simulations of the SMWT in Zemax	75
F	Results for the SMWT	76
G	Simulations of the ALMA and LLAMA 12-m antenna in Zemax	83
H	Results for the 12-m antenna	86

List of Tables

2.1	Review of existing submillimeter and terahertz heterodyne arrays.	26
2.2	Review of existing millimeter heterodyne arrays.	27
3.1	Main parameters of the Cassegrain antenna of the SMWT (Mini).	29
3.2	Main parameters of the corrugated horn antenna of the SMWT (Mini). . . .	30
3.3	Illumination efficiency and percentage of power that passes through the main hole. Parameters for the outer pixel using the actual characteristics of the feed horn of the SMWT.	32
3.4	Illumination efficiency and percentage of power that passes through the main hole. Parameters for the outer pixel using the actual electrical characteristics of the feed horn of the SMWT.	35
3.5	Illumination efficiency and percentage of power that passes through the main hole. Parameters for the outer pixel using an hypothetical beam waist for the SMWT.	36
4.1	Main parameters of the 12-m Cassegrain antenna of ALMA.	41
4.2	Illumination efficiency and percentage of power that passes through the hole of the primary reflector for a 12-m ALMA antenna. Parameters for the outer pixel using the actual characteristics of the feed horn+lens+ellipsoidal mirror of Band-3	43
4.3	Parameters for the GBT of ALMA.	46
4.4	Illumination efficiency and percentage of power that passes through the main hole of a 12-m ALMA antenna. Parameters for the outer pixel using the GBT designed for Band-3	47
4.5	Beam distortion in curved mirrors due to reflections and cross polarization in ALMA's GBT	48
4.6	Parameters for the GBT of LLAMA.	55
4.7	Illumination efficiency and percentage of power that passes through the main hole of a 12-m LLAMA antenna. Parameters for the outer pixel using the GBT designed for W band.	56
4.8	Beam distortion in curved mirrors due to reflections and cross polarization in LLAMA's GBT	56
4.9	Comparative analysis of hexagonal cameras with 7, 19, 37 and 61 pixels. . .	57
A.1	Main parameters and formulas to define a conic section.	68
B.1	Examples of ABCD matrix.	69

D.1	Main parameters of the Cassegrain antenna of the SMWT (Mini) in inches. .	73
D.2	Main parameters of the corrugated horn antenna of the SMWT (Mini) in inches.	74
E.1	Parameters (in mm) for simulate the SMWT in Zemax.	75
G.1	Parameters (in mm) for simulate the ALMA 12-m antenna in Zemax.	83
G.2	Parameters (in mm) for simulate the ALMA 12-m antenna in Zemax and the Gaussian Beam Telescope designed.	84
G.3	Parameters (in mm) for simulate the LLAMA 12-m antenna in Zemax and the Gaussian Beam Telescope designed.	85

List of Figures

1.1	Electromagnetic spectrum and the atmospheric windows.	3
2.1	Electromagnetic propagation theories.	5
2.2	Reflection and refraction.	6
2.3	Image formation using geometrical optics.	7
2.4	Scheme of ray transfer.	8
2.5	Optics versus quasi-optics focusing.	9
2.6	Gaussian beam parameters.	10
2.7	Near and far-field regions of radiation.	11
2.8	A 2-D radiation pattern of an antenna.	12
2.9	Cassegrain antenna and its main parameters.	13
2.10	Dual-mode horn.	15
2.11	Parameters of a conical corrugated horn antenna.	16
2.12	Lens geometry.	17
2.13	Paraboloid and ellipsoid geometry.	19
2.14	Heterodyne receiver: DSB, SSB, 2SB.	21
2.15	Gaussian Beam Telescope configuration.	23
2.16	Hexagonal distribution of seven pixels for a focal plane array.	24
3.1	Scheme of the proposed 7 pixel circular array.	29
3.2	SMWT in Zemax	31
3.3	SMWT. Huygens PSF for the central pixel (d=0 mm).	31
3.4	SMWT. Huygens PSF for an outer pixel (d=42.42 mm).	33
3.5	Percentage of power due to truncation and illumination efficiency (spillover and taper).	33
3.6	Seven beams at the hole of the main reflector.	34
3.7	Illumination efficiency as a function of displacement off-axis for the SMWT (using actual horn antenna).	34
3.8	SMWT. Huygens PSF for an outer pixel (d=31.54 mm).	35
3.9	SMWT. Huygens PSF for an outer pixel (d=21.63 mm).	36
3.10	Beam propagation plot on axis for the SMWT at 115 GHz.	37
4.1	Scheme of ALMA 12-m antenna and its cryostat.	43
4.2	Upper view of the actual cryostat of ALMA. 10 bands are placed in the available space.	44
4.3	Model of the optical system proposed for ALMA heterodyne receiver.	46

4.4	Huygens PSF obtained in Zemax for the central and 29.28-mm offset pixel of ALMA model.	47
4.5	Beam propagation plot on axis for ALMA's GBT at 100 GHz.	48
4.6	3-D model of the intermediate optical system designed for ALMA Band-3.	49
4.7	Mechanical model of the cartridge inside the cryostat.	49
4.8	Coupling Efficiency as a function of the displacement, tilt and offset.	50
4.9	Scheme of a Cassegrain Telescope with three possibilities of focal planes.	53
4.10	Scheme of LLAMA 12-m antenna and its cryostat.	54
4.11	Scheme of GBT designed for LLAMA 12-m antenna.	54
4.12	Huygens PSF and Wave-front function obtained in Zemax for the central and 13.01-mm offset pixel of LLAMA model.	56
4.13	Beam propagation plot on axis for LLAMA's GBT at 100 GHz.	57
4.14	3-D model of the intermediate optical system designed for LLAMA Band-3.	58
A.1	Conic sections.	68
C.1	Displacement of pixels in a hexagonal distribution.	72
C.2	Area compared to a hexagonal distribution over a single pixel.	72
D.1	Original blueprint of the horn antenna of the SMWT	74
F.1	Power through the main reflector hole of the SMWT (d=42.42 mm).	76
F.2	Power through the main reflector hole of the SMWT (d=31.54 mm).	77
F.3	Power through the main reflector hole of the SMWT (d=21.63 mm).	77
F.4	Beam Radius and Edge Taper at the secondary reflector of the SMWT as function of the beam waist w_0	78
F.5	Distribution of E for an outer pixel displaced 42.42 mm off axis and the secondary reflector border of the SMWT. Results for the current horn antenna.	79
F.6	Distribution of E for an outer pixel displaced 31.54 mm off axis and the secondary reflector border of the SMWT. Results for the current horn antenna with a thinner wall.	80
F.7	Distribution of E for an outer pixel displaced 21.63 mm off axis and the secondary reflector border of the SMWT. Results for a horn antenna with a beam waist of 6.8 mm.	81
F.8	Illumination efficiency as a function of the beam waist size and the displacement off the center for the SMWT.	82
H.1	Power through the main reflector hole of the 12-m ALMA antenna (d=58.56 mm).	86
H.2	Power at the secondary reflector of the 12-m ALMA antenna (d=58.56 mm).	87
H.3	Beam Radius and Edge Taper at the secondary reflector of the 12-m ALMA antenna as a function of the beam waist w_0	87
H.4	Distribution of E for a central and an outer pixel displaced 58.56 mm off axis and the secondary reflector border of the 12-m ALMA antenna. Results for 100 GHz and an edge taper of 10.9 dB.	88