

Contents

1	Introduction	1
1.1	Objectives	2
1.1.1	General Objective	2
1.1.2	Specific Objectives	2
1.2	Methodology	2
2	Background	3
2.1	Semiconductor Physics	3
2.1.1	Semiconductor Microstructure	3
2.1.2	Carrier Transport Phenomena	9
2.2	PN junction	12
2.3	Photovoltaic Solar Cell	13
2.3.1	Design	15
2.4	Properties of Gallium Arsenide	16
2.5	Hydrodynamic Stability	17
2.6	Hot Spot in PV Solar Cells	18
3	Model Description	23
3.1	Physical parameters	24
3.2	Assumptions	25
3.3	Boundary Conditions	26
3.4	Non-dimensional Form	27
4	Resolution Method	29
4.1	Perturbation Theory	29
4.2	Disturbed System	31
4.2.1	Zero order system	32
4.2.2	First Order System	32
4.3	Linear stability analysis	33
4.3.1	Steady-State System	33
4.3.2	Transient-state System	35
4.3.3	Boundary Conditions	37
4.3.4	Integration Methods	38
4.3.5	Temporal Eigenvalues	40
5	Results	41
5.1	Validity of Results	41
5.1.1	Main Code Tolerance	41

5.1.2	Transient-state Code Conditions	43
5.2	Data Processing	46
5.2.1	Range of Allowed Eigenvalues	47
5.3	Sensitivity Analysis	49
5.3.1	Solution at Thermal Equilibrium	49
5.3.2	Variation in Temperature	51
5.3.3	Variation in Longitude	57
5.3.4	Variation in applied voltage	59
5.4	Surface Temperature	61
6	Conclusions and Future Work	64
6.1	Conclusions	64
6.2	Future Work	65
	Bibliography	66

List of Tables

2.1	Portion of periodic table related to semiconductors [10].	4
3.1	Physical properties for GaAs [34]	25

List of Figures

2.1	Bravais lattices [11].	5
2.2	Conventional unit cube for GaAs [12].	5
2.3	Energy bands in Silicon crystal with a diamond lattice structure [10].	6
2.4	Representation of electron and holes [10].	6
2.5	Schematic energy-momentum diagram for Si and GaAs [13].	7
2.6	Actual bidimensional energy-momentum diagram for GaAs and Si [12]	8
2.7	Fermi distribution function for various temperatures [10].	8
2.8	a)Uniformly doped p-type and n-type semiconductors.b)Electric field in the depletion region and the energy band diagram of a PN junction in thermal equilibrium [10].	12
2.9	Band diagram of solar cell.Generated electron-hole pairs drift across the depletion region [14].	13
2.10	I-V Characteristic of solar cell [14].	14
2.11	Schematic diagram of solar cell layers [15].	15
2.12	Hot spot temperature profile, TCO layer [23].	18
2.13	Equivalent circuit of PN junction.	20
2.14	IR mapping triple junction a-Si:H [25]	20
2.15	Temperature distribution over sample at 2[suns] [25].	21
2.16	Simulated temporal temperature as a function of thermal conductivity χ [25].	22
3.1	Device scheme with boundary conditions [33].	26
4.1	Steady-state variables distribution in space.	34
5.1	Significant digits in steady state code.	42
5.2	Positive eigenvalues from Runge Kutta 2nd order.	44
5.3	Relative error from Runge Kutta 2nd order.	44
5.4	Positive eigenvalues from Runge Kutta 4th order.	45
5.5	Relative error from Runge Kutta 4th order.	45
5.6	General transient response representation in time.	46
5.7	Reference time t_0	48
5.8	Allowed range of characteristic time.	48
5.9	Allowed range of characteristic time-zoom.	49
5.10	Eigenvalues at thermal equilibrium, $q_L = 0$	50
5.11	Eigenvalues at thermal equilibrium, $q_L > 0$	50
5.12	Positive eigenvalues at $T_C = 650[K]$, $V_{app} = 0.4[V]$, $L = 4[\mu m]$	52
5.13	Characteristic time at $T_C = 650[K]$, $V_{app} = 0.4[V]$, $L = 4[\mu m]$	52
5.14	Allowed range at $T_C = 650[K]$, $V_{app} = 0.4[V]$, $L = 4[\mu m]$	53
5.15	Positive eigenvalues at $T_L = 300[K]$, $V_{app} = 0.4[V]$, $L = 4[\mu m]$	54

5.16	Characteristic times at $T_L = 300[K]$, $V_{app} = 0.4[V]$, $L = 4[\mu m]$	54
5.17	Allowed range at $T_L = 300[K]$, $V_{app} = 0.4[V]$, $L = 4[\mu m]$	55
5.18	Positive eigenvalues at $T_C - T_L = 150[K]$, $V_{app} = 0.4[V]$, $L = 4[\mu m]$	56
5.19	Characteristic time at $T_C - T_L = 150[K]$, $V_{app} = 0.4[V]$, $L = 4[\mu m]$	56
5.20	Allowed range at $T_C - T_L = 150[K]$, $V_{app} = 0.4[V]$, $L = 4[\mu m]$	57
5.21	Positive eigenvalues at $T_L = 300[K]$, $T_C = 450[K]$, $V_{app} = 0.4[V]$	58
5.22	Characteristic time at $T_L = 300[K]$, $T_C = 450[K]$, $V_{app} = 0.4[V]$	58
5.23	Allowed range at $T_L = 300[K]$, $T_C = 450[K]$, $V_{app} = 0.4[V]$	59
5.24	Positive eigenvalues at $T_L = 300[K]$, $T_C = 450[K]$, $L = 4[\mu m]$	60
5.25	Characteristic time at $T_L = 300[K]$, $T_C = 450[K]$, $L = 4[\mu m]$	60
5.26	Allowed range at $T_L = 300[K]$, $T_C = 450[K]$, $L = 4[\mu m]$	61
5.27	Thermal resistance at varying irradiation [42].	62
5.28	Temperature and efficiency varying irradianations [43].	62
5.29	Global horizontal irradiation [44].	63