Table of content

Acronyms **xiv**

1 Introduction **1**
- 1.1 Motivation and background . . . 2
  - 1.1.1 Definition of the problem . . . 3
  - 1.1.2 Proposed solution . . . 3
- 1.2 Hypotheses . . . 4
- 1.3 Objectives . . . 5
  - 1.3.1 General objectives . . . 5
  - 1.3.2 Specific objectives . . . 5
- 1.4 Thesis outline . . . 6

2 Theoretical framework **7**
- 2.1 Technical Concepts . . . 7
  - 2.1.1 Low Power Wide-Area Networks . . . 7
  - 2.1.2 Sigfox . . . 9
  - 2.1.3 Static Context Header Compression and Fragmentation . . . 10
- 2.2 Related Work . . . 16
  - 2.2.1 Network performance studies . . . 16
  - 2.2.2 Fragmentation in LPWAN . . . 17
  - 2.2.3 SCHC definition . . . 17
  - 2.2.4 SCHC performance studies . . . 18
  - 2.2.5 SCHC implementations . . . 20

3 Methodology **21**
- 3.1 Software development process . . . 21
- 3.2 Performance metrics . . . 23
  - 3.2.1 Justification . . . 23
  - 3.2.2 Modeling process . . . 24
- 3.3 Data collection and analysis . . . 24
  - 3.3.1 Experimental design . . . 24
  - 3.3.2 Experimental setup . . . 26
  - 3.3.3 Data analysis . . . 27

4 SCHC-over-Sigfox implementation **29**
- 4.1 Module description . . . 29
- 4.2 Simulation . . . 31
- 4.3 Real deployment . . . 32

5 Performance metrics **34**

5.1 SCHC F/R process overview . . . 34
5.2 Average number of uplink messages per SCHC transmission . . . 37
5.2.1 Justification . . . 37
5.2.2 Theoretical model . . . 38
5.2.3 Validation . . . 39
5.2.4 Empirical adjustment . . . 40
5.3 Rate of successful SCHC transmissions . . . 42
5.3.1 Justification . . . 42
5.3.2 Theoretical model . . . 43
5.3.3 Validation . . . 43
5.3.4 Empirical adjustment . . . 45

6 Results **47**
6.1 Average number of uplink messages sent per SCHC transmission . . . 47
6.1.1 Simulation results (non-aborting scenario) . . . 47
6.1.2 Simulation results (base scenario) . . . 50
6.1.3 Real deployment results . . . 52
6.2 Rate of successful SCHC transmissions . . . 55
6.2.1 Simulation results . . . 55
6.2.2 Simulation results with different timeouts . . . 58
6.2.3 Real deployment results . . . 58

7 Analysis **61**
7.1 Average number of uplink messages per SCHC transmission . . . 61
7.1.1 Semi-empirical model and non-aborting scenario . . . 61
7.1.2 Base scenario . . . 62
7.1.3 Real deployment . . . 63
7.1.4 Interpretation . . . 64
7.2 Rate of successful SCHC transmissions . . . 64
7.2.1 Semi-empirical model and simulation results . . . 64
7.2.2 Results with different timeouts . . . 65
7.2.3 Real deployment . . . 65
7.2.4 Interpretation . . . 65
7.3 General observations . . . 66

8 Conclusions and Future Work **67**
8.1 Conclusions . . . 67
8.2 Limitations and future work . . . 69

Bibliography **74**

Annexes **74**

A Publications derived from this thesis **75**

B Implementation UML diagrams **76**

C Validation of $N_{U_T}(p)$ **79**

D Validation of $N_U(p)$ over the non-aborting scenario **84**

E Validation of $N_U(p)$ over the base scenario **93**

F Real deployment results of N_U **97**

G Validation of $r_{S_T}(p)$ **102**
H Validation of $r_S(p)$ **107**
I Real deployment results of r_S **116**