

Contents

1	Introduction and Motivation	1
1.1	Motivation of the study	3
1.2	Problem statement	4
1.3	Contributions	4
2	Background and state of the art	5
2.1	Wireless networks in underground mines	5
2.2	Mobile Ad Hoc Networks	6
2.3	Delay Tolerant Networks	7
2.4	DTN Protocols Taxonomy	9
2.4.1	Controlled replicative protocols	10
2.4.2	Unlimited replicative protocols	11
2.4.3	Forwarding protocols	12
2.5	Mobility models	14
2.6	Common mobility models	15
2.6.1	Random Mobility Models	15
2.6.2	Map-Constrained Mobility Models	16
2.6.3	Social Mobility Models	17
2.6.4	Composite Mobility Models	18
2.7	Limitations of existing mobility models in mining scenarios	18
3	Modelling mobility in an underground mine	19
3.1	Extraction process in underground mines	19
3.1.1	Block Caving	19
3.2	Related work and references	20
3.2.1	Additional observations	21
3.3	Description of the proposed simplified model	22
3.3.1	Description of Areas	23
3.3.2	Description of Nodes	24
3.4	Validation and limitations of the model	24
3.5	BonnMotion simulator	25
3.6	Implementation details	26
3.6.1	Visibility Graph	27
3.6.2	Node Implementation	27
3.6.3	Restrictions	27
3.6.4	Input	28

3.7	Analysis of the model	28
3.7.1	Path Availability and Partitioning	29
3.7.2	Inter-Contact times and Link Duration	31
3.8	Conclusion	33
4	DTN performance in Underground Mines	38
4.1	Node mobility analysis	38
4.1.1	Number of encounters	39
4.1.2	Encounters by node type	40
4.1.3	General mobility observations	40
4.2	DTN Routing Protocols Evaluation	41
4.2.1	TheONE Simulator	41
4.2.2	Comparative evaluation in a Simple Mine Scenario	42
4.3	Limitations and opportunities for improvement	44
4.4	Conclusion	45
5	Node localization in Underground Environments	46
5.1	Mining localization	46
5.2	Localization strategies	47
5.2.1	Estimation of position	47
5.2.2	Physical considerations	48
5.3	Proposed Map Generation Strategy	49
5.3.1	Local map generation	50
5.3.2	Global map generation	51
5.4	Implementation details	54
5.4.1	Information timeout	54
5.4.2	Positioning Hierarchy	54
5.4.3	Map Generation Process	55
5.5	Map Performance	55
5.5.1	Position estimation error	56
5.5.2	Node coverage	57
5.5.3	Aggregated node coverage	57
5.6	Conclusions	58
6	Design and implementation of the protocol	59
6.1	MaxProp review	59
6.1.1	Delivery Likelihood estimation	59
6.1.2	Packet prioritization	60
6.2	MineProp design	61
6.2.1	Node type and area discovery	61
6.2.2	Message origin	62
6.2.3	Candidate rating	62
6.2.4	Delivery likelihood	63
6.3	Implementation details	64
6.3.1	Configuration Parameters	64
6.3.2	Message information	65
6.3.3	Area discovery	65

6.3.4	Cost estimation	65
6.3.5	Candidate rating	66
6.4	Protocol evaluation	66
6.4.1	Delivery probability	66
6.4.2	Delay	67
6.4.3	Overhead	67
6.4.4	Parameter choice	68
6.5	Conclusions	70
7	Conclusions and Future Work	71
7.1	Contributions	71
7.2	Projections and future work	72
7.3	Conclusion	73
8	Bibliography	74

List of Figures

2.1	Behavior of a disrupted ad hoc network in time [66].	7
2.2	Taxonomy of DTN Protocols.	9
2.3	Binary Spray strategy for 7 copies.	10
2.4	Calculation of path costs in MaxProp between nodes A and D [8].	12
2.5	Random ORBIT model [23].	13
2.6	Taxonomy of Mobility Models.	15
3.1	Layout of block/panel caving extraction area [52]	20
3.2	Timetable for nodes I_1 and I_2 through areas C , E_1 and E_2	21
3.3	Maintenance and Extraction areas representation.	23
3.4	Process to obtain the optimal route.	27
3.5	Diagrams of test scenarios.	29
3.6	Path availability and Node degree per Scenario.	30
3.7	Partitioning degree and Number of partitions per Scenario.	35
3.8	ICTs histograms of different scenarios.	36
3.9	LD histograms of different scenarios.	37
4.1	Number of encounters in 50 node scenario.	39
4.2	HeatMap of encounters by node ID: 1-8 are LHDs, 9-40 are OP, 41-50 are SU.	40
4.3	Delivery Probability for different protocols.	42
4.4	Delay for different protocols.	43
4.5	Overhead for different protocols.	44
5.1	Obstruction in LOS scenario [9].	49
5.2	Position of node j gives information for node k correction.	52
5.3	Node k in range with static nodes.	53
5.4	Current area detection through distance to static nodes.	53
5.5	Position estimation average error.	56
5.6	Average node coverage.	57
5.7	Average aggregated node coverage.	58
6.1	Area calculation using distance d_{ks_1} between a node k and static nodes s_1	61
6.2	Packet Delivery Rate for different protocols.	67
6.3	Delay for different protocols.	68
6.4	Overhead for different protocols.	68

List of Tables

3.1	ICTs Statistics.	33
3.2	LD Statistics.	34
4.1	Unique node encounters for Simple Mine Scenario.	39
4.2	Simulation parameters.	42
6.1	Parameters for MineProp protocol evaluation.	66
6.2	Packet delivery rate for different values of β and κ	69
6.3	Delay for different values of β and κ	69
6.4	Overhead for different values of β and κ	69