See discussions, stats, and author profiles for this publication at: https://www.researchgate.net/publication/317300463

Investigation of Charged Particles Radiation Moving in a Homogeneous Dispersive Medium

Article *in* International Journal of Engineering, Transactions B: Applications · May 2017 DOI: 10.5829/idosi.ije.2017.30.05b.07

| ITATIONS | READS |
|---------------------------------|-------------------------------|
| | 59 |
| authors, including: | |
| Arash Dehzangi | Saeid Kakooei |
| Northwestern University | Universiti Teknologi PETRONAS |
| 67 PUBLICATIONS 299 CITATIONS | 45 PUBLICATIONS 274 CITATIONS |
| SEE PROFILE | SEE PROFILE |
| Masih Ghasmi | Farzaneh Saadati |
| National University of Malaysia | University of Chile |
| 29 PUBLICATIONS 104 CITATIONS | 9 PUBLICATIONS 5 CITATIONS |
| SEE PROFILE | SEE PROFILE |
| | |

Some of the authors of this publication are also working on these related projects:

Complex optical waveguides View project

Project

SMART NANOCONTAINERS: FUNDAMENTALS AND EMERGING APPLICATIONS View project

All content following this page was uploaded by Arash Dehzangi on 02 June 2017.



International Journal of Engineering

TECHNICAL NOTE

Journal Homepage: www.ije.ir

Investigation of Charged Particles Radiation Moving in a Homogeneous Dispersive Medium

A. Dehzangi^{*a}, A. R. Ghaffari^b, S. Kakooei^{*c}, M. Ghasemi^d, F. Saadati^e, H. Soleimani^f

^a Center for Quantum Devices, Department of Electrical Engineering and Computer Science, Northwestern University, Evanston, Illinois, USA

^b Department of Physics, Arsanjan Branch, Islamic Azad University, Arsanjan, Fars, Iran

^c Mechanical Engineering Department, Universiti Teknologi PETROPNAS, Malaysia

^d Institute of Microengineering and Nanoelectronics (IMEN), Universiti Kebangsaan Malaysia, Selangor, Malaysia

^e Center for Advanced Research in Education (CIAE), University of Chile, Santiago, Chile

f Fundamental & Applied Sciences Department, Universiti Teknologi PETROPNAS, Malaysia

PAPER INFO

Paper history: Received 16 February 2017 Received in revised form 03 March 2017 Accepted 10 March 2017

Keywords: Cherenkov Radiation Quantum Computing Drude-lorents Model Homogeneous Dispersive Medium

ABSTRACT

In this work, we use Drude-Lorents model description to study the radiation of a charged particles moving in a homogeneous dispersive medium. A suitable quantized electromagnetic field for such medium is utilized to obtain proper equations for energy loss of the particle per unit length. The energy loss is separately calculated for transverse and longitudinal components of the filed operators. The calculations show that the longitudinal component of the field operators contributes in electron radiation, when dielectric function is exceedingly dependent on the frequency. It is also shown that when the dispersion is not included, the obtained equations are in a good agreement with previous results. For negligible dispersion, the contribution of the field's longitudinal component tends to zero and at the end the results are in agreement with Ginsberg's calculations. This calculation can reveal a development for the field's quantization for permeable dielectric background medium.

doi: 10.5829/idosi.ije.2017.30.05b.07

1. INTRODUCTION

The Cherenkov radiation is known as electron emission (electromagnetic radiation), when a charged particle passes through a medium with a velocity larger than the phase velocity of the light in that specific medium [1, 2]. There are several mechanisms involved in Cherenkov radiation by which a high-energy subatomic particle- e.g. electron- can reach to an energetic equilibrium with its surrounding environment and determine how radiation is produced from these interactions. The Cherenkov radiation has been highly regarded at the beginning of the twentieth century for its importance in nuclear physics and cosmic ray[3]. Recently, the Cherenkov radiation has drawn attention in several fields and applications. In combination with electromagnetic simulations in electronics [4-6], it has several applications in meta-material optoelectronics, photonic nanostructures, imaging of medical isotopes and ultra-fast laser pulses [7-11]. The behavior of electromagnetic radiations can often be incorporated into continuous, effective material parameters [12] or ultra-small scale materials [13] with different approaches [14, 15]. As a recent comprehensive study, Shaffer et al. presented a review study about different aspects of utilizing Cherenkov light in nanotechnology [16].

Frank and Tamm [17] have investigated classical calculations of Cherenkov radiation, by deriving radiation intensity per unit time from the solution of electrodynamics equations in a particular medium. In their calculations, radiation intensity is considered as the Poynting vector flux [18] across the cylindrical surface, which hypothetically surrounds the electron trajectory [19].

^{*}Corresponding Author's Email: arash.dehzangi@northwestern.edu (A. Dehzangi)

Please cite this article as: A. Dehzangi, A. R. Ghaffari, S. Kakooei, M. Ghasemi, F. Saadati, H. Soleimani, Investigation of Charged Particles Radiation Moving in a Homogeneous Dispersive Medium, International Journal of Engineering (IJE), TRANSACTIONSB: Applications Vol. 30, No. 5, (May 2017) 678-683

On the other hand, Ginsberg reported the quantum computing of Cherenkov radiation [20, 21] with a good agreement with Pavel Cherenkov observation, who had originally discovered and analyzed the nature of this particular radiation. In this quantum mechanical approach, the theory is based on the conventional framework of quantum electrodynamics. Due to the limitation in fields' quantization calculation at the same time, dissipative property of the background medium is not taken into account. It should be noted that the Ginsberg's calculations have been presented within quantized fields whose dielectric permittivity variation with frequency was insignificance. Recently, the fields' quantization for casual permeable dielectric background medium has been developed [22, 23], given to that it can be interesting to recalculate the Ginsberg quantum calculation for the fields with quantized disperse medium.

In this letter, first the Drude-Lorents model is reviewed and since quantum mechanical methods are offered for our calculations, then we take a glance at the electromagnetic field quantization in dispersive medium. By using the applicable model and electromagnetic fields calculation for such a medium, the behavior of the medium will be explained. To perform such analyses, the Fermi golden rule is implemented to calculate the rate of energy loss per unit length with the same method that was used by Ginsberg. Both longitudinal and transverse components of the electric field are shown to contribute in the radiation process. Unlike the previous classical and quantum mechanical calculations, the field's longitudinal component has important role in the rate of energy loss. However, it is observed that for negligible dispersion, this contribution tends to zero and at the end the results are in agreement with Ginsberg's calculations.

2. DRUDE- LORENTS MODEL

The Drude- Lorents model for a dielectric function in environments where damping is negligible, predicts following equation [24]:

$$\varepsilon(\omega) = \frac{\omega_L^2 - \omega^2}{\omega_0^2 - \omega^2} \tag{1}$$

when $\omega_L^2 = \omega_0^2 + \omega_p^2$, ω_0 is inherent frequency and ω_P is plasma frequency. In some cases where the environment has negligible damping, this equation can also be written as [24, 25]:

$$\varepsilon(\omega) = \frac{k^2 c^2}{\omega^2} \tag{2}$$

where k is the wave-vector and C is the speed of light. When the right side of these two previous equations are equated with each other, it can be seen that for each k value there are two values for ω , as ω_+ and ω_- , which are shown in Figure 1.

3. ELECTRIC FILED QUANTIZATION EQUATIONS

All of the field operators are typically categorized into two separate parts as the transverse and longitudinal, and each of them should have a vector potential. The transverse component of the vector potential in dispersive medium is as following [26, 27]:

$$\hat{A}^{T}(\vec{r},t) = \left(\frac{\hbar}{16\pi^{3}\varepsilon_{0}}\right)^{\frac{1}{2}} \int d^{3}\vec{k} \sum_{\lambda} \sum_{\pm} \left(\frac{v_{g}(\omega_{\pm})}{\omega_{\pm}\eta^{2}(\omega_{\pm})v_{p}(\omega_{\pm})}\right)^{\frac{1}{2}} \left\{ \tilde{e}_{\lambda}(\vec{k}) \hat{e}_{\lambda}^{\pm}(\vec{k}) e^{-i\left(\omega_{\pm}t-\vec{k},\vec{r}\right)} \right\}$$
(3)

when $v_p(\omega)$ and $v_g(\omega)$ are the phase velocity and group velocity, respectively, $\varepsilon_r = \eta^2$ and *H.C* is referring to the Hermit conjugate of the function. It should be noted that $\tilde{e}_{\lambda}(\vec{k})$ is the polarization vector in the plane perpendicular to \vec{k} , when $\hat{c}_{\lambda}^{\pm}(\vec{k})$ is a boson operator and both are applicable to the following equation:

$$\left[\hat{c}_{\lambda}^{\pm}\left(\vec{k}\right),\hat{c}_{\lambda'}^{\pm}\left(\vec{k}'\right)\right]=\delta_{\lambda\lambda'}\delta\left(\vec{k}-\vec{k}'\right)$$
(4)

The longitude operator of the quantized vector potential is equal to:

$$\hat{A}^{L}(\vec{r},t) = -\left(\frac{\hbar}{16\pi^{3}\varepsilon_{0}\omega_{L}^{2}\eta(\omega_{L})\eta'(\omega_{L})}\right)^{\frac{1}{2}} \times \int d^{3}\vec{k} \left\{ \tilde{k}\hat{c}(\vec{k})e^{-i(\omega_{L\pm}t-\vec{k}.\vec{r})} \right\}$$
(5)

which $\omega_{\rm L}$ is the only root of the equation $\eta^2(\omega) = 0$, and \tilde{k} is the unit vector along the wave vector.




Figure 1. The graph of k vs ω , when imaginary part of the dielectric function tends to zero

4. FINDING THE RATE OF ENERGY LOSS FOR A MOVING CHARGE PARTICLE IN THE FIELD TRANSVERSE COMPONENT

To find the rate of energy dissipation, the Ginsberg method is implemented [28]. First, the Fermi golden rule is used to find the probability of emitted photons per unit time for each moving charged particle, which is expressed as the following:

$$\Gamma = \frac{2\pi}{\hbar} \left| V_{fi} \right|^2 \delta \left(E_f - E_i \right) \tag{6}$$

 $|i\rangle$ and $|f\rangle$ are the initial and final state of the system, respectively. It is assumed that the charged particle is initially moving with the momentum of $\hbar \vec{q}$ or velocity of $v = \frac{\hbar q}{\lambda}$, which leads to the emission of a photon with

the momentum of $\hbar k$. Accordingly, it can be written:

$$\left|f\right\rangle = \left\langle 1\left|\left\langle \vec{q} - \vec{k}\right|\right\rangle, \ \left|i\right\rangle = \left\langle 0\left|\left\langle \vec{q}\right|\right\rangle\right\rangle \tag{7}$$

The term in the bracket of Equation (6) is the energy difference between the first and final states for a particle travelling with the mass of m and charge of Q, which means:

$$E_{f} - E_{i} = \frac{\hbar^{2}}{2m} \left| \vec{q} - \vec{k} \right|^{2} + \hbar \omega_{k} - \frac{\hbar^{2} q^{2}}{2m}$$
(8)

Then, the perturbation potential is only considered as the first-order terms of vector potential [29], and we have:

$$V_{fi} = \left\langle f \left| -\frac{Q}{m} \vec{P} \cdot \vec{A} \right| i \right\rangle \tag{9}$$

According to the above equations, the probability of emitted photons per unit time for the transverse component of vector potential (Γ^{T}) for the Equation (6) can be written as:

$$\Gamma^{(T)} = \frac{Q^2}{8\pi^2 m^2 \varepsilon_0 \omega_{\pm}} \frac{v_g(\omega_{\pm})}{\eta^2(\omega_{\pm}) v_p(\omega_{\pm})} \times \left| \left\langle \vec{q} - \vec{k} \middle| \vec{P} \cdot \widetilde{e}_{\lambda} e^{-i\vec{k}\cdot\vec{r}} \middle| \vec{q} \right\rangle \right|^2 \times$$

$$\frac{1}{\hbar k v} \delta \left(\cos \theta - \frac{\hbar k}{2mv} - \frac{\omega_{\pm}}{k v} \right)$$
(10)

where θ is the angle between the initial velocity of the particle, before emission, and the direction of the emitted photon. Now it is time to calculate the energy loss of the particle per unit length, from the following relation:

$$\frac{dW}{dx} = \frac{1}{\nu} \sum_{\pm} \sum_{\lambda} d^3 \vec{k} \hbar \omega_{\pm} \Gamma$$
(11)

After substituting the Equation (10) into the above relation for transverse component of Γ (as Γ^{T}), and using the definition of the volume element in k^3 space, the energy loss is calculated as following [30]:

$$\frac{dW^{(T)}}{dx} = \frac{Q^2}{4\pi\varepsilon_0} \sum_{\pm} \int dk \frac{kv_g(\omega_{\pm})}{\eta^2(\omega_{\pm})v_p(\omega_{\pm})} \times \left(1 - \left(\frac{\hbar k}{2mv} + \frac{\omega_{\pm}}{kv}\right)^2\right)$$
(12)

4. 1. Finding the Integration Limits and Minimum of Speed By means of using Dirac delta function term in Equation (12), the integration limits can be determined. According to the concept of delta function and the value of the cosine, which is between +1 and -1, one can write:

$$\omega_{\pm} \le -\frac{\hbar}{2m}k^2 + \nu k \tag{13}$$

From the intersection of the curve in Figure 1 with the parabola formula, from the right side of Equation (13), we reach to an inequality to determine the value of k(Figure 2).

The numerical calculations of Equation (13) are as following:

i) Several numerical calculations show that the parabola from the right side of the Equation (13) does not intercept with the ω_+ curve. Then for dispersive media, ω_{-} is the only term which is entered in the calculations.

ii) For the mediums with $\frac{\omega_p}{\omega_0} \approx 1$, i.e. condensed environments 24 , the ω_{-} curve quickly reaches its limit value (ω_0 in Figure 2), and this helps to be able to find the value of k.

By having
$$\omega_{-} = \omega_{0}$$
, the intercept of $-\frac{\hbar}{2m}k^{2} + vk$

(parabola) and ω_{-} (curve), as k_{+} and k_{-} , can be obtained as following:

$$k_{\pm} = \frac{mv}{\hbar} \left(1 \pm \sqrt{1 - \frac{2\hbar\omega_0}{mv^2}} \right) \tag{14}$$




Figure 2. The intersection curve of $-\frac{\hbar}{2m}k^2 + vk$ and ω_-

These two values define the integration limits in Equation (12). It should be noted that according to the existing tables, k_{+} and k_{-} are always real [25]. Now, Equation (12) can be rewritten as following:

$$\frac{dW^{(T)}}{dx} = \frac{Q^2}{4\pi\varepsilon_0} \times \int_{k_-}^{k_-} dk \frac{kv_g(\omega_-)}{\eta^2 v_p(\omega_-)} \left(1 - \left(\frac{\hbar k}{2mv} + \frac{\omega_-}{kv}\right)^2\right)$$
(15)

Regarding the fact that $\omega_{-} = \omega_{0}$, Equation (13) leads to determination of the minimum speed of the charged particle, at which a photon emission can be occurred.

$$v \ge \frac{c}{n} + \frac{\hbar}{2m}k\tag{16}$$

4. 2. Reaching to a State with a Negligible Dispersion In this section, the state with the negligible dispersion is considered, and it is shown that the equation obtained in Equation (15) is in well agreement with the classical calculation [17], as well as Ginzberg quantum calculations [31]. By implementing the following equation [7]:

$$v_{p}(\omega_{-}) = \frac{c}{\eta(\omega_{-})}$$

$$v_{g}(\omega_{-}) = \frac{2c\eta(\omega_{-})}{\omega_{-}\frac{\partial}{\partial\omega} \left(\eta^{2} - \left(\frac{kc}{\omega}\right)^{2}\right)_{\omega=\omega_{-}}}$$

$$\eta^{2}(\omega_{-}) = n^{2} = \varepsilon(\omega_{-})$$
(17)

Then, Equation (15) can be written as:

$$\frac{dW^{(T)}}{dx} = \frac{Q^2}{2\pi\varepsilon_0} \times \int_{k_-}^{k_-} \frac{\partial}{\partial\omega} \left(\eta^2(\omega) - \left(\frac{kc}{\omega}\right)^2 \right)_{\omega=\omega_-} \times \left(1 - \left(\frac{\hbar k}{2mv} + \frac{\omega_-}{kv}\right)^2 \right)$$
(18)

where $\frac{\partial n}{\partial \omega} \approx 0$, then the value of $\omega_{\rm L}$ and ω_0 should get close together. In this case, the allowed region for integration is between 0 and k_o , and for this area (as shown in Figure 2), the relationship between *k* and ω is almost linear, as in $\omega = \omega_{-} = \frac{kc}{n}$, where *c* and *n* are constant. Accordingly, Equation (15) can be written as:

$$\frac{dW^{(T)}}{dx} = \frac{Q^2}{2\pi\varepsilon_0} \int d\omega \frac{\omega^2 \varepsilon(\omega)}{\frac{\partial}{\partial \omega} (\omega^2 \varepsilon(\omega))} \times \left(1 - \frac{c^2}{n^2 v^2} \left(1 + \frac{\hbar \omega n^2}{2mc^2}\right)^2\right)$$
(19)

Ginzberg obtained the same expression in his calculation [31].

4. 3. Whether All the Energy Loss of the Moving Charged Particles Originated from the Transverse Fields' Component? If we apply the previous procedure for the longitudinal component of the electric field, then equation for the energy loss of the particle per unit length can be written:

$$\frac{dW^{(L)}}{dx} = \frac{Q^2}{2\pi\varepsilon_0 \omega_L} \frac{\partial}{\partial \omega} \varepsilon(\omega) \times \left\{ \frac{\hbar^2 k^4}{16m^2 v^2} + \frac{\hbar^2 k^4 \omega_L}{2mv^2} + \frac{\omega_L^2}{v^2} \ln(k) \right\}_{k=k_-(\omega_L)}^{k=k_+(\omega_L)}$$
(20)

The important question is why in previous calculations the contribution of such energy has not been included. The answer is that whatever obtained in previous calculations was related to the contribution of the transverse component of the field operators. Here, it is shown that the longitudinal component of field operators contributes in electron radiation, when the dielectric function is highly frequency dependent. In previous works, the dielectric function was considered with low dependency in frequency, where the frequency value was considered as $\omega_L \approx \omega_T$. At the frequencies close to ω_L , the above equation will be converted to the form below:

$$\frac{dW^{(T)}}{dx} = \frac{Q^2}{4\pi\varepsilon_0} \frac{\omega_L^2 - \omega_T^2}{\omega_L^2} \times \left\{ \frac{\hbar^2 k^4}{16m^2 v^2} + \frac{\hbar^2 k^4 \omega_L}{2mv^2} + \frac{\omega_L^2}{v^2} \ln(k) \right\}_{k=k_-(\omega_L)}^{k=k_+(\omega_L)}$$
(21)

This shows that if the dispersion is negligible, then $\frac{dW}{dx}$ tend to zero in agreement to the previous works.

5. CONCLUSIONS

In this study, the radiation of charged particles moving in a homogeneous dispersive medium was studied. During the energy loss calculations, two frequencies were found for each k value. We presented that ω_{-} has important role in calculations but ω_{+} has no contribution in calculations. It is also found that if the dispersion in medium is significant, then not only the field's transverse component, but also longitudinal component has contribution in energy losses. This is the case that was not derived in Frank and Tamm classical calculation or Ginsberg quantum calculations.

6. ACKNOWLEDGMENT

Authors would like to thank Professor Reza Matloob from the physics department of University of Kerman and Professor Mahmood Barati from the department of physics at Shiraz University for their great supports and assistance.

7. REFERENCES

- Cerenkov, P., "Visible radiation produced by electrons moving in a medium with velocities exceeding that of light", *Physical Review*, Vol. 52, No. 4, (1937).
- Mirzoyan, R., "Brief history of ground-based very high energy gamma-ray astrophysics with atmospheric air Cherenkov telescopes", Astroparticle Physics, Vol. 53, (2014), 91-99.
- Engelfried, J., "Cherenkov light imaging—Fundamentals and recent development", Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment, Vol. 639, No. 1, (2011), 1-6.
- Ghasemi, M., Choudhury, P. K., Dehzangi, A., "Nanoengineered thin films of copper for the optical monitoring of urine – a comparative study of the helical and columnar nanostructures", *Journal of Electromagnetic Waves and Applications*, Vol. 29, (2015), No.17, 2321-2329.
- Dehzangi, A., Larki, F., Naseri, M. G., Navasery, M., Majlis, B. Y., Razip Wee, M. F., Halimah, M. K., Islam, M. S., Md Ali, S. H., Saion E., "Fabrication and simulation of single crystal p-type Si nanowire using SOI technology. *Applied Surface Science*, Vol. 334, (2015), 87-93.
- Dehzangi, A., Larki F., Md Ali, S. H., Hutagalung, S. D., Islam, M. S., Hamidon, M. N., Menon, S., Jalar, A., Hassan, J., Majlis, B. Y., "Study of the side gate junctionless transistor in accumulation region", *Microelectronics International*, Vol. 33, No. 2, (2016), 61-67.
- De Abajo, A. J. G., Pattantyus-Abraham, A. G., Zabala, N., Rivacoba, A., Wolf, M. O., Echenique, P. M, "Cherenkov effect as a probe of photonic nanostructures" *Physical Review Letters*, Vol. 91, No. 14, (2003), 143902/1-143902/4.
- Saito, H., Kurata, H., "Formation of a hybrid plasmonic waveguide mode probed by dispersion measurement". *Journal* of *Applied Physics*, Vol. 11, No. 13, (2015).
- Lohrmann, C., Zhang, H., Thorek, D. L., Desai, P., Zanzonico, P. B., O'Donoghue, J., Irwin, C. P., Reiner, T., Grimm, J., Weber, W. A," Cerenkov Luminescence Imaging for Radiation Dose Calculation of a 90Y-Labeled Gastrin-Releasing Peptide Receptor Antagonist", *Journal of Nuclear Medicine*, Vol. 65, No. 5, (2015), 805-811.
- Song, T., Liu, X., Qu, Y., Liu, H., Bao, C., Leng, C., Hu, Z., Wang, K., Tian, J, "A Novel Endoscopic Cerenkov

Luminescence Imaging System for Intraoperative Surgical Navigation", *Molecular Imaging*, Vol. 14, (2015), 443-49.

- Wahlstrand, J. K., Merlin, R., "Cherenkov radiation emitted by ultrafast laser pulses and the generation of coherent polaritons", *Physical Review B - Condensed Matter and Materials Physics*, Vol. 68, No. 5, (2003), 543011-5430112.
- Navasery, M., Halim, S. A., Dehzangi, A., Soltani, N., Bahmanrokh, G., Kamalianfar, A., Pan, K. Y., Chang, S. C., Chen, S. K., Lim, K. P., Kechik, M. A, "Electrical properties and conduction mechanisms in La_{2/3}Ca_{1/3}MnO₃ thin films prepared by pulsed laser deposition on different substrates". *Applied Physics A*, Vol. 116, No. 4, (2014), 1661-1668.
- Soltani, N., Dehzangi, A., Saion, E., Majlis, B. Y., Zare, M. R., Kharazmi, A., Navasery, M., "Influence of exposure time on structural, optical and electrical properties of zinc sulphide nanoparticles synthesized by microwave technique" *Chalcogenide Letters*, Vol. 10, No. 1, (2013), 27-37.
- Hoang, A. M., Dehzangi, A., Adhikary, S., Razeghi, M., "High performance bias-selectable three-color Short-wave/Midwave/Long-wave Infrared Photodetectors based on Type-II InAs/GaSb/AISb superlattices". *Scientific Reports*, Vol. 6, (2016).
- Soltani, N., Dehzangi, A., Kharazmi, A., Saion, E., Yunus, W., Majlis, B. Y., Zare, M. R., Gharibshahi, E., Khalilzadeh, N., "Structural, optical and electrical properties of ZnS nanoparticles affecting by organic coating", *Chalcogenide Letters*, Vol. 11, No. 2, (2014), 79-90.
- Shaffer, T. M., Pratt, E. C., Grimm, J., "Utilizing the power of Cerenkov light with nanotechnology", *Nature Nanotechnology*, Vol. 12, No. 2, (2017), 106-117.
- Tamm, I., Frank, I., "Coherent radiation of fast electrons in a medium", *Dokl. Akad. Nauk SSSR*, (1937).
- Pardy, M., "The two-dimensional Vavilov–Cerenkov radiation in LED", *Results in Physics*, Vol. 5 (2015), 69-71.
- 19. Matloob, R., Ghaffari, A., "Cerenkov radiation in a causal permeable medium", *Physical Review A*, Vol. 70, No. 5, (2004).
- Bohm, D., "Quantum Theory", New York: Dover Publications, (2012).
- Ginzburg, V. L., "A Scientific Autobiography—an Attempt", *The Physics of a Lifetime.*, Springer, (2001), 309-347.
- Dung, H. T., Buhmann, S. Y., Knoll, L., Welsch, D. G., Scheel, S. Kastel, J., "Electromagnetic-field quantization and spontaneous decay in left-handed media", *Physical Review A* -*Atomic, Molecular, and Optical Physics*, Vol. 68, No. 4, (2003), 043816/1-043816/15.
- Matloob, R., "Electromagnetic field quantization in a linear isotropic permeable dielectric medium", *Physical Review A* -*Atomic, Molecular, and Optical Physics*, Vol. 70, No. 2, (2004), 022108-1-022108-9.
- Hehl, F. W., Obukhov, Y. N., "Foundations of classical electrodynamics: Charge, flux, and metric", Springer Science & Business Media, Vol. 33, (2012).
- Greiner, W., "Classical electrodynamics", Springer Science & Business Media, (2012).
- Matloob, R., "Electromagnetic field quantization in an absorbing mediu", *Physical Review A*, Vol. 60, No. 1, (1999).
- Crosse, J. A., Fuchs S., Buhmann S. Y., "Electromagnetic Green's function for layered topological insulators", *Physical Review A*, Vol. 96, No. 2, (2015).
- Ginzburg, V. L., "Radiation by uniformly moving sources (Vavilov-Cherenkov effect, transition radiation, and other phenomena)", *Physics-Uspekhi*, Vol. 39, No. 10, (1996), 973-982.

 Reitz, J. R., Milford F. J., Christy R. W., "Foundations of electromagnetic theory", Addison-Wesley Publishing Company, Boston, (2008). Courier Corporation, Massachusetts, (2014).

- Akhiezer, A. I., Akhiezer, I. A., Polovin, R. V., "Plasma Electrodynamics: Linear Theory", Vol. 68, Elsevier, (2013).
- 30. Harris, E. G., "A pedestrian approach to quantum field theory",

Investigation of Charged Particles Radiation Moving in a Homogeneous **TECHNICAL** Dispersive Medium

A. Dehzangi^a, A. R. Ghaffari^b, S. Kakooei^{*c}, M. Ghasemi^d, F. Saadati^e, H. Soleimani^f

^a Center for Quantum Devices, Department of Electrical Engineering and Computer Science, Northwestern University, Evanston, USA

^b Department of Physics, Arsanjan Branch, Islamic Azad University, Arsanjan, Fars, Iran

^c Mechanical Engineering Department, Universiti Teknologi PETROPNAS, Malaysia

^d Institute of Microengineering and Nanoelectronics (IMEN), Universiti Kebangsaan Malaysia, Selangor, Malaysia

^e Center for Advanced Research in Education (CIAE), University of Chile, Santiago, Chile

f Fundamental & Applied Sciences Department, Universiti Teknologi PETROPNAS, Malaysia

PAPER INFO

Paper history: Received 16 February 2017 Received in revised form 03 March 2017 Accepted 10 March 2017

Keywords: Cherenkov Radiation Quantum Computing Drude-lorents Model Homogeneous Dispersive Medium در این مقاله با استفاده از مدل درود لورنتس برای توصیف محیط، به تشریح تابش ذرات بار دارمتحرک در محیط های پاشنده همگن می پردازیم. در اینجا ازمیدانهای الکترومغناطیسی کوانتیزه شده مناسب برای چنین محیط هایی بهره گرفته شده است و فرمول بندی مناسبی جهت آهنگ اتلاف انرژی ذره در واحد طول ارائه می شود. اتلاف انرژی به طور جداگانه برای مولفه های عملگر میدان الکتریکی محاسبه میشود. و این محاسبات نشان می دهد که مولفه طولی عملگر های میدان بیشترین سهم را در تابش الکترون ایفا می کند. نتایج نشان می دهند که وقتی از پاشندگی صرف نظر شود, روابط به دست آمده با نتایج قبلی به خوبی در توافق است. این محاسبات می تواند پیشرفتی را برای تحلیل و محاسبه معادلات کوانتیزه سازی میدانها الکترومغناطیسی برای محیط های با پس زمینه دی الکتریک نفوذ پذیر را نشان دهد, که به نوبه خود رهیافت های جدیدی را برای کاربردهای روز آمد در فوتونیک و تصویر نگاری پزشکی معرفی میکند

چکيده

doi: 10.5829/idosi.ije.2017.30.05b.07