

Contents

1	Introduction	1
1.1	General objectives	2
1.2	Specific objectives	2
1.3	Document Structure	3
2	Bibliographic review	4
2.1	Mobile Platform (Husky A200 Clearpath)	4
2.2	Sensors	5
2.2.1	TOPCON HIPERIÓN GPS [1]	5
2.2.2	Stereo camera (Bumblebee®XB3[2])	7
2.2.3	LIDAR (VLP-16[3])	7
2.2.4	RADAR (Acumine 94 Ghz[4])	8
2.3	State of the art	9
2.3.1	SLAM	9
2.3.2	Graph-SLAM [5]	11
2.3.3	ORB-SLAM [6]	13
2.3.4	LOAM (Lidar Odometry and mapping) [7]	16
3	Methodology	19
3.1	Sensors connection	19
3.2	Collecting data	20
3.3	Computing The SLAM algorithm	20
3.4	Comparison with ground truth	20
3.5	Working Schedule	21
4	Generating the data set	23
4.1	GPS configuration	23
4.1.1	Connecting the GPS to the computer	24
4.1.2	Verifying the data	24
4.2	Collecting the data	29
4.2.1	Test data	29
4.2.2	Verifying the final trajectory	31
5	Data Processing	35
5.1	ORB-SLAM	35
5.2	LOAM	36
5.3	Comparison	37

6 Conclusion	41
Bibliography	43